

# **FN FNS, FNX TRIJICON RMR SIGHT MOUNT - EGW FN FNS, FNX TRIJICON RMR SIGHT MOUNT**

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



## **Attributes**

- Name: [EGW FN FNS, FNX TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000563
- Mfr. No.: 49504
- Colour: Black
- Material: Aluminum
- Model: FNS,FNX
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: FN
- Delivery weight: 0.031kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116744

## **Item details**

Made in USA

# Table of Contents

- Startpage
- FN FNS, FNX TRIJICON RMR SIGHT MOUNT Safety Instruction Guide
- About Us

# FN FNS, FNX TRIJICON RMR SIGHT MOUNT Safety Instruction Guide

## Introduction

Thank you for choosing the FN FNS, FNX TRIJICON RMR SIGHT MOUNT by EGW. This guide provides essential safety instructions and installation details to ensure the safe and effective use of your product. Please read this document thoroughly before use.

## General Safety Guidelines

- **Product Safety:** Ensure the product is used as intended. This mount is designed for specific firearm models and should not be used with incompatible firearms.
- **Enhanced Recalls:** Stay informed about any recalls related to this product. Regularly check for updates on the EU's Safety Gate platform.
- **Online Shopping Safety:** If purchased online, ensure the retailer complies with safety regulations.
- **Vulnerable Groups:** Keep this product out of reach of children and ensure that it is used only by individuals with appropriate knowledge and experience.
- **EU Contact Point:** For safety inquiries, please refer to the designated EU contact point provided by your retailer.
- **Rapid Alerts:** Be vigilant for safety alerts regarding this product via the Safety Gate system.

## Specific Safety Precautions for Use

### • Hazard Identification:

- Improper installation may lead to the red dot sight becoming loose or detaching, posing a risk of injury.
- Ensure that the mounting hardware is secure before use to avoid accidents.

### • Avoiding Hazards:

- Always check the compatibility of your firearm with this mount before installation.
- Do not modify the mount or firearm in any way that could compromise safety.
- Use the appropriate tools to install the mount to ensure a secure fit.

### • Age Specific Warnings:

- This product should only be installed and used by individuals aged 18 years or older.
- Ensure that younger individuals are supervised when handling firearms or firearm accessories.

## Instructions for Installation and Usage

### • Tools Required:

- 5/64" Allen wrench (not included)
- Blue Loctite (not included)

### • Installation Steps:

1. Remove the rear sight from your firearm.
2. Install the EGW Sight Mount in the dovetail.
3. Tighten the set screw (if applicable).

4. Place the red dot sight on the EGW Sight Mount.
  - Note: Placing a small piece of paper between the red dot sight and the mount will facilitate easier removal and protect the sight from Loctite.
5. Apply blue Loctite to the provided mounting screws.
6. Torque the mounting screws to 15 in/lbs.
7. Ensure that both Flat Head Cap Screws are securely tightened.

- **Usage Tips:**

- Regularly inspect the mount and screws for tightness and integrity.
- If you notice any looseness or damage, discontinue use immediately and consult a professional.

## Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Contact your local waste management authority for guidance on proper disposal methods.

## Contact Information for Further Support

For any questions or concerns regarding the safety and use of the FN FNS, FNX TRIJICON RMR SIGHT MOUNT, please refer to the contact information provided by your retailer or manufacturer. Ensure that you have your product details at hand for efficient assistance.

By following the instructions and guidelines in this manual, you can ensure the safe and effective use of your FN FNS, FNX TRIJICON RMR SIGHT MOUNT. Thank you for your attention to safety.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)