

H&K USP TRIJICON RMR SIGHT MOUNT - EGW H&K USP TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW H&K USP TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000564
- Mfr. No.: 49505
- Colour: Black
- Material: Aluminum
- Model: USP
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Heckler & Koch
- Delivery weight: 0.033kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116751

Item details

Made in USA

Table of Contents

- Startpage
- H&K USP Trijicon RMR Sight Mount Safety Instructions
- About Us

H&K USP Trijicon RMR Sight Mount Safety Instructions

Introduction

Thank you for choosing the H&K USP Trijicon RMR Sight Mount. This product is designed to enhance your shooting experience by providing a secure platform for mounting your Trijicon RMR red dot sight. To ensure your safety and the proper functioning of the sight mount, please read and follow these safety instructions carefully.

General Safety Guidelines

- Ensure safe use of the sight mount by following all instructions.
- Regularly inspect the sight mount for any signs of wear or damage.
- Do not use the sight mount if it appears damaged or compromised.
- Always keep the sight mount out of reach of children and vulnerable individuals.
- If you encounter any issues or concerns regarding the product, report them to the appropriate authorities.

Specific Safety Precautions for Use

• Installation Precautions:

- Always wear safety glasses while installing or modifying the sight mount.
- Ensure the firearm is unloaded before beginning installation.
- Use only the provided mounting hardware to secure the sight mount.

• Usage Precautions:

- Avoid using the sight mount in extreme weather conditions that may affect its integrity.
- Regularly check the tightness of the mounting screws to prevent the sight from loosening during use.
- Do not exceed the recommended torque of 15 in/lbs when securing the mounting screws.

• Disposal Precautions:

- Dispose of any packaging materials responsibly and in accordance with local regulations.
- Do not dispose of the sight mount in fire, as it may cause harmful emissions.

Instructions for Installation and Usage

1. Remove the Rear Sight:

- Carefully remove the rear sight from your firearm.

2. Install the EGW Sight Mount:

- Place the EGW Sight Mount into the dovetail of the firearm.
- Ensure proper alignment before proceeding.

3. Tighten Set Screw (if applicable):

- If your mount includes a set screw, tighten it securely to prevent movement.

4. Place the Red Dot Sight:

- Position the Trijicon RMR red dot sight on the EGW Sight Mount.
- For easier removal in the future, place a small piece of paper between the sight and the mount to prevent Loctite from adhering.

5. Apply Blue Loctite:

- Apply blue Loctite to the provided mounting screws to secure them in place.

6. Torque Mounting Screws:

- Using a 5/64" allen wrench, torque the mounting screws to 15 in/lbs.

7. Final Check:

- Ensure everything is securely fastened and that the sight is properly aligned.

Disposal Instructions

- Dispose of all packaging materials in accordance with local waste disposal regulations.
- If the sight mount is no longer needed, it should be disposed of in a manner that complies with local environmental regulations.

Contact Information for Further Support

For any inquiries regarding the safety or use of the H&K USP Trijicon RMR Sight Mount, please refer to the appropriate local authorities or consumer safety organizations.

By following these safety instructions, you can ensure the safe and effective use of your H&K USP Trijicon RMR Sight Mount. Thank you for your attention to safety and enjoy your enhanced shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk