

EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT - EGW EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000565
- Mfr. No.: 49506
- Colour: Black
- Material: Aluminum
- Model: HK45, HK45 Compact, P30, P30L, P30sk, Tanfoglio Witness, VP40, VP9
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: EAA, Heckler & Koch
- Delivery weight: 0.035kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116768

Item details

Made in USA

Table of Contents

- Startpage
- EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT Safety Instructions Guide
- About Us

EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT Safety Instructions Guide

Introduction

Thank you for choosing the EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT. This product is designed to enhance your shooting experience by allowing the installation of a Trijicon RMR red dot sight on your firearm. To ensure safe and effective use, please read this safety instruction guide carefully.

General Safety Guidelines

- Always ensure that your firearm is unloaded before installing or removing the sight mount.
- Keep the sight mount and all components out of reach of children and unauthorized users.
- Inspect the sight mount and mounting hardware for any signs of damage before installation.
- Use only the recommended mounting hardware provided with the sight mount.
- Follow all local laws and regulations regarding the use of firearms and accessories.
- If you are unsure about any aspect of installation or usage, seek assistance from a qualified gunsmith.

Specific Safety Precautions for Use

- Ensure that the firearm is pointed in a safe direction at all times during installation.
- Do not attempt to install the sight mount while the firearm is loaded.
- Be cautious of sharp edges on the mount and screws during installation to avoid injury.
- Avoid overtightening the screws, as this may damage the mount or the firearm.
- Use blue Loctite on the mounting screws to prevent loosening during use.
- Do not modify the sight mount or firearm in any way that is not specified in the installation instructions.

Instructions for Installation and Usage

1. Remove the rear sight:

- Carefully remove the existing rear sight from your firearm.

2. Install the EGW Sight Mount:

- Place the EGW Sight Mount into the dovetail of your firearm.

3. Tighten the set screw:

- If applicable, tighten the set screw to secure the mount in place.

4. Place the red dot sight:

- Position the Trijicon RMR red dot sight on the EGW Sight Mount.
- To facilitate future removal, place a small piece of paper between the red dot sight and the sight mount to keep Loctite off the sight.

5. Apply blue Loctite:

- Apply blue Loctite to the provided mounting screws to secure the red dot sight.

6. Torque mounting screws:

- Tighten the mounting screws to a torque of 15 in/lbs.

- Note: The screws included with this mount require a 5/64" allen wrench for installation.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- When disposing of the sight mount or any components, ensure that they are not accessible to children or pets.
- Check local regulations for specific disposal guidelines regarding aluminum and other materials.

Contact Information for Further Support

For any safety inquiries or further assistance regarding the EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT, please refer to the contact details provided with your product packaging or visit the manufacturer's website.

By following these guidelines and instructions, you can ensure the safe use of the EAA TANFOGLIO WITNESS TRIJICON RMR SIGHT MOUNT. Thank you for your attention to safety and enjoy your enhanced shooting experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk