

H&K VP9/40, P30, HK45 TRIJICON RMR SIGHT MOUNT - EGW H&K VP9/40, P30, HK45 TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW H&K VP9/40, P30, HK45 TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000566
- Mfr. No.: 49507
- Colour: Black
- Material: Aluminum
- Model: HK45, HK45 Compact, P30, P30L, P30sk, VP40, VP9
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Heckler & Koch
- Delivery weight: 0.034kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 127mm
- UPC: 841370116829

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for H&K VP9/40, P30, HK45 Trijicon RMR Sight Mount
- About Us

Safety Instruction Guide for H&K VP9/40, P30, HK45 Trijicon RMR Sight Mount

Introduction

Thank you for choosing the H&K VP9/40, P30, HK45 Trijicon RMR Sight Mount. This guide provides important safety instructions and information to ensure the safe and effective use of this product. Please read and follow all instructions carefully.

General Safety Guidelines

- Always ensure the firearm is unloaded before installing or removing the sight mount.
- Use the sight mount only for its intended purpose as described in this guide.
- Inspect the sight mount regularly for any signs of damage or wear. Do not use if damaged.
- Keep the sight mount out of reach of children and unauthorized users.
- Follow all local laws and regulations regarding firearm accessories and modifications.
- Report any unsafe conditions or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the mounting surface is clean and free of debris before installation.
- Do not exceed the recommended torque specifications for mounting screws (15 in/lbs).
- Use blue Loctite on the provided mounting screws to prevent loosening during use.
- Avoid using excessive force when tightening screws to prevent stripping.
- If you experience any difficulty during installation, consult a qualified gunsmith.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm.

2. Install the EGW Sight Mount

- Insert the EGW Sight Mount into the dovetail of your firearm.
- Ensure it is seated properly.

3. Tighten Set Screw (If Applicable)

- If your mount includes a set screw, tighten it securely.

4. Place the Red Dot Sight

- Position the Trijicon RMR red dot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the sight mount.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws before installation.

6. Torque Mounting Screws

- Use a 5/64" allen wrench to tighten the screws to a torque of 15 in/lbs.

7. Final Inspection

- Inspect the installation to ensure everything is secure before use.

Disposal Instructions

- Dispose of the sight mount and packaging materials in accordance with local regulations.
- Do not dispose of the sight mount in household waste. Check for designated recycling or disposal facilities.

Contact Information for Further Support

For any questions or concerns regarding the H&K VP9/40, P30, HK45 Trijicon RMR Sight Mount, please refer to the manufacturer's contact information provided with your product packaging.

By following these safety instructions and guidelines, you can ensure the safe and effective use of your H&K VP9/40, P30, HK45 Trijicon RMR Sight Mount. Thank you for your attention and commitment to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk