

# KIMBER ADJUSTABLE REAR SIGHT TRIJICON RMR SIGHT MOUNT - EGW KIMBER ADJUSTABLE REAR TRIJICON RMR SIGHT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



## Attributes

- Name: [EGW KIMBER ADJUSTABLE REAR TRIJICON RMR SIGHT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000575
- Mfr. No.: 49516
- Colour: Black
- Material: Aluminum
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Kimber
- Delivery weight: 0.036kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 133mm
- UPC: 841370116577

## Item details

Made in USA

# Table of Contents

- Startpage
- KIMBER ADJUSTABLE REAR SIGHT TRIJICON RMR SIGHT MOUNT USER MANUAL
- About Us

# KIMBER ADJUSTABLE REAR SIGHT TRIJICON RMR SIGHT MOUNT USER MANUAL

## Introduction

Thank you for purchasing the Kimber Adjustable Rear Sight Trijicon RMR Sight Mount. This user manual provides important safety instructions and guidelines to ensure the proper use and installation of the product. Please read this manual carefully before using the product to ensure safe operation and compliance with all safety regulations.

## General Safety Guidelines

- Ensure that the sight mount is compatible with your firearm before installation.
- Always follow the manufacturer's instructions for installation and usage.
- Regularly inspect the sight mount for any signs of wear or damage.
- Use only the recommended tools and hardware for installation.
- If you encounter any issues during installation or use, contact a qualified gunsmith or the manufacturer for assistance.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe conditions or accidents to the relevant authorities.

## Specific Safety Precautions for Use

- Do not attempt to modify or alter the sight mount in any way.
- Ensure that your firearm is unloaded before installing or removing the sight mount.
- Always use protective eyewear when handling firearms and during installation.
- Be aware of your surroundings and ensure that you are in a safe environment when using your firearm.
- Check that all screws are properly tightened before use to prevent accidents.
- If you experience any difficulties with the sight mount, cease use immediately and seek assistance.

## Instructions for Installation and Usage

### 1. Remove the Rear Sight

- Ensure your firearm is unloaded.
- Carefully remove the existing rear sight from your firearm.

### 2. Install the EGW Sight Mount

- Place the EGW Sight Mount into the dovetail of your firearm.
- Tighten the set screw (if applicable) to secure the mount in place.

### 3. Mount the Red Dot Sight

- Place the Trijicon RMR red dot sight on the EGW Sight Mount.
- For easier removal in the future, place a small piece of paper between the red dot sight and the sight mount to prevent Loctite from adhering to the sight.

### 4. Apply Loctite

- Apply blue Loctite to the provided mounting screws.

### 5. Torque the Screws

- Use a torque wrench to tighten the mounting screws to 15 in/lbs.

## 6. Final Checks

- Ensure that both flat head cap screws are properly installed for the Trijicon RMR.

## Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- When disposing of the sight mount, ensure it is done in an environmentally friendly manner.
- Follow local guidelines for the disposal of aluminum products.

## Contact Information for Further Support

For any questions or concerns regarding the Kimber Adjustable Rear Sight Trijicon RMR Sight Mount, please refer to the manufacturer's contact information provided with your product packaging or visit the manufacturer's website for further assistance.

**Disclaimer:** This user manual is intended for informational purposes only. The manufacturer is not liable for any misuse or improper installation of the product. Always adhere to local laws and regulations regarding firearm accessories.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)