

SIG SAUER P220-229, 320 TRIJICON RMR SIGHT MOUNT - EGW SIG SAUER P220-229, 320 TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

THIS MOUNT DOES NOT WORK WITH ANY SIG OPTICS READY PISTOLS (P320 X-CARRY ETC.) Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mount fits (including but not limited to): Sig #8 Sights P220 P224 P225 P225-A1 P226 P227 P228 P229 P238 P239 P245 P320 P938 SP2022 M11-A1 MK25 Bersa Thunder UC Series (9/40/45) Bersa Thunder HC Series (9/40/45) FN 509 This mount does not fit: Sig 1911s Any Optics Ready Sigs i.e. P226 Legion RX, P229 RX, P320 X-Carry etc. P210 Target P365 (The dovetail cut is too deep to work with our mount) FN 509 Tactical Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW SIG SAUER P220-229, 320 TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000577
- Mfr. No.: 49518
- Colour: Black
- Material: Aluminum
- Model: 509,P220,P224,P225,P226,P227,P228,P229,P238,P239,P245,P320,P938,SP2022
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: FN,Sig Sauer
- Delivery weight: 0.031kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116553

Item details

Made in USA

Table of Contents

- Startpage
- SIG SAUER P220229, 320 TRIJICON RMR SIGHT MOUNT Safety Instructions
- About Us

SIG SAUER P220229, 320 TRIJICON RMR SIGHT MOUNT Safety Instructions

Introduction

Thank you for choosing the SIG SAUER P220229, 320 TRIJICON RMR SIGHT MOUNT. This guide provides essential safety information and instructions to ensure the safe and effective use of this product. Please read this manual carefully before installation and use.

General Safety Guidelines

- Ensure that the mount is compatible with your firearm model before installation.
- Always handle firearms safely and responsibly, following all local laws and regulations.
- Inspect the mount and all components for damage before use. Do not use if any parts are damaged.
- Keep the mount and all accessories out of reach of children and unauthorized users.
- If you experience any issues during installation or use, cease use immediately and seek assistance.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- This mount does not work with any SIG opticsready pistols, including but not limited to P320 XCARRY.
- Ensure that the rear sight is completely removed before installing the mount.
- Use the specified mounting hardware only. Do not substitute with other screws or components.
- Apply blue Loctite to the provided mounting screws to ensure secure installation.
- Torque mounting screws to 15 in/lbs to prevent loosening during use.
- Do not attempt to modify the mount or the firearm in any way.
- If you are unsure about installation, consult a qualified gunsmith.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount into the dovetail of your firearm.

3. Tighten Set Screw (if applicable)

- Ensure the set screw is tightened securely.

4. Place the Red Dot Sight

- Position the red dot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the mount to keep Loctite off the sight.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to prevent loosening.

6. Torque Mounting Screws

- Using a 5/64" allen wrench, torque the mounting screws to 15 in/lbs.

Disposal Instructions

- Dispose of the product and packaging materials in accordance with local regulations.
- Do not dispose of electronic components in regular waste. Check for electronic waste recycling programs in your area.

Contact Information for Further Support

For any questions or concerns regarding the SIG SAUER P220229, 320 TRIJICON RMR SIGHT MOUNT, please refer to your local authorized dealer or manufacturer's website for further assistance.

By following these guidelines and instructions, you can ensure the safe and effective use of the SIG SAUER P220229, 320 TRIJICON RMR SIGHT MOUNT. Thank you for your attention to safety and responsible firearm handling.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk