

S&W REVOLVER TRIJICON RMR SIGHT MOUNT - EGW S&W REVOLVER TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW S&W REVOLVER TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000578
- Mfr. No.: 49519
- Colour: Black
- Material: Aluminum
- Model: K Frame,L Frame,N Frame,X Frame
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Smith & Wesson
- Delivery weight: 0.039kg
- Shipping height: 25mm
- Shipping width: 83mm
- Shipping length: 140mm
- UPC: 841370116546

Item details

Made in USA

Table of Contents

- Startpage
- S&W REVOLVER TRIJICON RMR SIGHT MOUNT Safety Instruction Guide
- About Us

S&W REVOLVER TRIJICON RMR SIGHT MOUNT Safety Instruction Guide

Introduction

Thank you for choosing the S&W Revolver Trijicon RMR Sight Mount. This guide provides important safety information, installation instructions, and proper usage guidelines to ensure your safety and the effective operation of your product. Please read this document carefully before use.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Always follow the manufacturer's instructions for installation and maintenance.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly check the product for any signs of wear or damage before use.
- Report any unsafe products or accidents to local authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Only use the mount with compatible red dot sights: Trijicon RMR and Holosun HS507C.
- This mount does not fit Rock Island 1911s. Ensure compatibility before installation.
- Ensure that the rear sight is properly removed and the mount is securely installed to avoid accidents.
- Use blue Loctite on the provided mounting screws to prevent loosening during operation.
- Always torque mounting screws to 15 in/lbs to maintain secure attachment.
- Avoid placing any foreign objects between the red dot sight and the mount, except for the recommended piece of paper for easier removal.
- Do not attempt to modify the mount or the firearm in any way that could compromise safety.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm to make way for the EGW Sight Mount.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount into the dovetail slot where the rear sight was located.

3. Tighten Set Screw

- If applicable, tighten the set screw to secure the mount in place.

4. Place the Red Dot Sight

- Position your Trijicon RMR red dot sight onto the EGW Sight Mount.
- For easier removal of the sight, place a small piece of paper between the sight and the mount to prevent Loctite from adhering to the sight.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to ensure they remain secure.

6. Torque Mounting Screws

- Using a 5/64" allen wrench, torque the mounting screws to 15 in/lbs for optimal security.

7. Final Check

- After installation, doublecheck that all screws are tightened and the red dot sight is secure before use.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- For electronic components, follow your local guidelines for electronic waste disposal.

Contact Information for Further Support

For any questions or concerns regarding the S&W Revolver Trijicon RMR Sight Mount, please refer to the manufacturer's website or customer service for assistance.

By following these guidelines and instructions, you can ensure the safe and effective use of your S&W Revolver Trijicon RMR Sight Mount. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk