

RUGER® MK I, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT - EGW RUGER® MKI, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW RUGER® MKI, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000580
- Mfr. No.: 49521
- Colour: Black
- Material: Aluminum
- Model: 22/45,Mark I,Mark II,Mark III,Mark IV,P85,P89,P97
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Ruger
- Delivery weight: 0.032kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 133mm
- UPC: 841370116522

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for RUGER® MK I, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT
- About Us

Safety Instruction Guide for RUGER® MK I, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT

Introduction

Thank you for choosing the RUGER® MK I, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT manufactured by EGW. This guide provides essential safety information and instructions to ensure the proper use and installation of your sight mount. Please read this document carefully to minimize risks and ensure safe operation.

General Safety Guidelines

- Always handle firearms and accessories with care and respect.
- Ensure the firearm is unloaded before installing or modifying any components.
- Use the product only for its intended purpose as outlined in this guide.
- Keep the sight mount and all accessories out of reach of children and unauthorized users.
- Regularly inspect the sight mount for wear or damage before each use.
- If you notice any defects or issues, discontinue use immediately and contact a qualified gunsmith or the manufacturer for assistance.
- Report any unsafe product experiences or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the red dot sight you are using is compatible with the EGW Sight Mount.
- When applying Loctite, avoid overapplication to prevent excess from interfering with the sight's operation.
- Always use the correct tools, specifically a 5/64" allen wrench, for installation to prevent damage to screws.
- Be cautious when tightening screws to avoid stripping them, which could lead to malfunction.
- If you are unsure about the installation process, seek assistance from a qualified professional.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the existing rear sight from your firearm.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount in the dovetail of your firearm.
- Ensure it is positioned correctly and securely.

3. Tighten the Set Screw

- If applicable, tighten the set screw using the appropriate tool to secure the mount in place.

4. Attach the Red Dot Sight

- Place the red dot sight onto the EGW Sight Mount.
- For easier removal in the future, insert a small piece of paper between the red dot sight and the mount to prevent Loctite from adhering to the sight.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to ensure a secure fit.

6. Torque Mounting Screws

- Using the 5/64" allen wrench, torque the mounting screws to a specification of 15 in/lbs.

7. Final Inspection

- After installation, doublecheck all screws and components to ensure everything is secure before using your firearm.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- If the sight mount or any components are damaged beyond repair, dispose of them responsibly, ensuring they do not pose a safety risk to others.

Contact Information for Further Support

For safety inquiries or assistance regarding this product, please consult the manufacturer's customer service or your local authorized dealer.

Please ensure you adhere to all safety guidelines and installation instructions to maximize your safety and the performance of your RUGER® MK I, II, III, IV, P85, P90 TRIJICON RMR SIGHT MOUNT. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk