

SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT - EGW SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000582
- Mfr. No.: 49523
- Colour: Black
- Material: Aluminum
- Model: XD,XD Mod 2,XD-E,XDM,XDS
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Springfield
- Delivery weight: 0.031kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116508

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT
- About Us

Safety Instruction Guide for SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT

Introduction

Thank you for choosing the SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT. This guide provides essential safety instructions and guidelines for the safe use, installation, and maintenance of your sight mount. It is important to read and understand this guide to ensure proper use and to minimize the risk of accidents.

General Safety Guidelines

- Always ensure the firearm is unloaded before installing or removing the sight mount.
- Use the sight mount only with compatible red dot sights (Trijicon RMR, Holosun HS507C).
- Keep the sight mount and its components out of reach of children.
- Regularly inspect the sight mount for signs of wear or damage.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the mounting hardware is securely tightened before use to prevent the sight from becoming loose during operation.
- Avoid using excessive force when tightening the screws to prevent damage to the mount or firearm.
- If you experience any issues with the sight mount, discontinue use immediately and seek assistance.
- Do not modify the sight mount or its components in any way, as this may compromise safety and functionality.
- Use caution when handling tools during installation to avoid injury.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm using appropriate tools.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount into the dovetail of your firearm.

3. Tighten Set Screw (if applicable)

- If your mount includes a set screw, tighten it securely to ensure stability.

4. Place the Red Dot Sight

- Position the red dot sight on the EGW Sight Mount. For easier removal, place a small piece of paper between the sight and the mount to prevent Loctite from adhering to the sight.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to secure the sight in place.

6. Torque Mounting Screws

- Torque the mounting screws to 15 in/lbs for optimal security.

7. Use Provided Hardware

- The mount includes two Flat Head Cap Screws for the Trijicon RMR. These screws require a 5/64" allen wrench for installation.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- Do not dispose of the sight mount in regular household waste. Follow local guidelines for the disposal of metal components.

Contact Information for Further Support

For any questions or concerns regarding the SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT, please refer to the manufacturer's website or contact their customer service department for assistance.

By following these safety guidelines and instructions, you can ensure the safe and effective use of your SPRINGFIELD XD TRIJICON RMR SIGHT MOUNT. Thank you for prioritizing safety in your shooting activities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk