

UNIVERSAL TRIJICON RMR SIGHT MOUNT - EGW UNIVERSAL .670" RADIUS SIGHT MOUNT FOR TRIJICON RMR BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Overall Height: .335" Radius: .468" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C .468" bottom radius mount. There should be a slight gap at the top of the radius between the receiver and the mount when mounted. The two spreads on this mount measure .500"-.505" and .8625". This should fit barrel/receiver diameters from .936"-1.350". .670" bottom radius mount. There should be a slight gap at the top of the radius between the receiver and the mount when mounted. The two spreads on this mount measure .500"-.505" and .8625" which should fit the receiver ring on the following guns: Common Applications for .670" bottom radius mount: Shotgun: Benelli Auto / Super Black Eagle / Vinchi, M2 (Will Work in the Front Set Only, 8-40 Screws) Benelli Supernova (Will Work in the Front Set Only, 8-40 AND Longer Screws) Browning A-Bolt 12 Gauge Savage 210 Savage 212 Savage 220 Stoeger M3000 / Stoeger M3500 (Will Work in the Front Set Only, 8-40 Screws) Winchester 1300 Winchester SXP Rifle: Remington 700, 722, 40x Remington 783 Remington 710/770 Remington xp 100 Remington 4, 6, 7400, 7615 (Front Set Only, 8-40 Screws) Savage arms centerfire models Winchester 70



Attributes

- Name: [EGW UNIVERSAL .670" RADIUS SIGHT MOUNT FOR TRIJICON RMR BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000584
- Mfr. No.: 49525
- Colour: Black
- Material: Aluminum
- Number of Bases: 1-Piece
- Style: Tactical
- Delivery weight: 0.039kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116485

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for UNIVERSAL TRIJICON RMR SIGHT MOUNT
- About Us

Safety Instruction Guide for UNIVERSAL TRIJICON RMR SIGHT MOUNT

Introduction

Thank you for choosing the UNIVERSAL TRIJICON RMR SIGHT MOUNT. This guide provides essential safety instructions and guidelines to ensure the safe use and installation of your product. Please read this guide carefully before use to maximize safety and performance.

General Safety Guidelines

- Always handle the sight mount with care to avoid injury.
- Ensure that the mounting surface is clean and free of debris before installation.
- Regularly inspect the sight mount for any signs of wear or damage.
- Do not exceed the specified barrel/receiver diameter limits.
- Keep the product out of reach of children and unauthorized users.
- If you experience any issues with the product, discontinue use immediately and seek assistance.

Specific Safety Precautions for Use

• Installation Safety:

- Use only the provided mounting hardware for installation.
- Tighten screws to the manufacturer's specifications to avoid loosening during use.
- Ensure that there is a slight gap at the top of the radius between the receiver and the mount when mounted.

• Compatibility:

- Confirm that your firearm is compatible with the .670" bottom radius mount before installation.
- Check that your firearm's specifications align with the listed common applications.

• Use of Tools:

- Use appropriate tools for installation to prevent damage to the mount or firearm.
- Avoid using excessive force when tightening screws.

• Storage:

- Store the sight mount in a dry and secure location when not in use.
- Avoid exposing the mount to extreme temperatures or moisture.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools: a screwdriver suitable for 632 screws.
- Ensure the workspace is clean and welllit.

2. Installation Steps:

- Remove any existing sights or mounts from the firearm.
- Align the sight mount with the mounting surface of the receiver.

- Insert the (2) 632 flat head screws into the designated holes and handtighten.
- Insert the (1) 632 set screw into the appropriate location.
- Use the screwdriver to tighten all screws securely, following the manufacturer's torque specifications.
- Confirm that the sight mount is firmly attached and that there is a slight gap at the top of the radius.

3. PostInstallation Check:

- Ensure that the mount does not obstruct the operation of the firearm.
- Test the stability of the mount before use by gently attempting to move it.

4. Usage:

- Follow all firearm safety guidelines when using the firearm equipped with the sight mount.
- Regularly check the mount for stability and tightness during use.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the sight mount is damaged beyond repair, follow local electronic waste disposal guidelines.
- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For any safety inquiries or concerns regarding the UNIVERSAL TRIJICON RMR SIGHT MOUNT, please refer to the EU contact point provided by the manufacturer or your retailer.

Conclusion

By following this safety instruction guide, you can ensure the proper use and installation of your UNIVERSAL TRIJICON RMR SIGHT MOUNT. Always prioritize safety and compliance with the EU General Product Safety Regulation (GPSR) for a secure and enjoyable experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk