

# RUGER PRECISION RIFLE HD SCOPE BASES - EGW RUGER PRECISION RIFLE HD SCOPE BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

Machined From: Solid 7075 T6 Aircraft Grade Aluminum Finish: Matte Black Only Compatible with Picatinny or Weaver scope rings. Mounting Hardware: #8-40 X 1/4 Screws and T-10 Wrench Included Torque Specs: 20 in/lbs This mount is made specifically for the Ruger Precision Rifle (RPR). The end of the rail with the number engraved is the front of the rail. This mount will not work on: Ruger Precision Rimfire Ruger Precision Magnum Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The cross slots are also machined the full width of the mount and gauged to MIL-STD 1913 specs maintaining tolerances of +/- .002". After machining; the mounts are tumbled and sand blasted. The aluminum mounts are Type III hard coat anodized for long lasting durability. The steel rails are Mil Spec parkerized for a durable rust resistant finish. We recommend: 0 MOA - if shooting 0-500 yards 30 MOA - if shooting 1000-1500 yards 40 MOA - if shooting 1500+ yards When zeroing your rifle with a 20 MOA mount, we recommend zeroing at 200 yards. Compatible with Picatinny or Weaver scope rings. Add EGW's HD Scope Rings to make it a complete package! From manufacturing to packaging, EGW's products are made with pride in the USA. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is available through our website and is sold separately).



Machined From: Solid 7075 T6 Aircraft Grade Aluminum Finish: Matte Black Only Compatible with Picatinny or Weaver scope rings. Mounting Hardware: #8-40 X 1/4 Screws and T-10 Wrench Included Torque Specs: 20 in/lbs This mount is made specifically for the Ruger Precision Rifle (RPR). The end of the rail with the number engraved is the front of the rail. This mount will not work on: Ruger Precision Rimfire Ruger Precision Magnum Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The cross slots are also machined the full width of the mount and gauged to MIL-STD 1913 specs maintaining tolerances of +/- .002". After machining; the mounts are tumbled and sand blasted. The aluminum mounts are Type III hard coat anodized for long lasting durability. The steel rails are Mil Spec parkerized for a durable rust resistant finish. We recommend: 0 MOA - if shooting 0-500 yards 30 MOA - if shooting 1000-1500 yards 40 MOA - if shooting 1500+ yards When zeroing your rifle with a 20 MOA mount, we recommend zeroing at 200 yards. Compatible with Picatinny or Weaver scope rings. Add EGW's HD Scope Rings to make it a complete package! From manufacturing to packaging, EGW's products are made with pride in the USA. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is available through our website and is sold separately).

## Attributes

- Name: [EGW RUGER PRECISION RIFLE HD SCOPE BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000599
- Mfr. No.: 80430
- Colour: Matte Black

- Elevation: 0 MOA
- Material: Aluminum
- Model: Precision Rifle
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Ruger
- Delivery weight: 0.158kg
- Shipping height: 25mm
- Shipping width: 95mm
- Shipping length: 273mm
- UPC: 841370117253

## **Item details**

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for RUGER PRECISION RIFLE HD SCOPE BASES
- About Us

# Safety Instruction Guide for RUGER PRECISION RIFLE HD SCOPE BASES

## Introduction

Thank you for choosing the RUGER PRECISION RIFLE HD SCOPE BASE. This guide provides essential safety instructions to ensure the proper use and installation of the product. Please read this guide thoroughly before use to ensure your safety and the safety of others.

## General Safety Guidelines

- **Product Safety:** Ensure safe use of the scope base by following all instructions provided in this guide. This product is designed for nonfood use and should be handled with care.
- **Enhanced Recalls:** Stay informed about any recall notices related to this product. In the event of a recall, you will be provided with free remedies for any dangerous products.
- **Online Shopping:** If you purchased this product online, you have the same safety protections as if you bought it in a physical store. Always ensure that online platforms comply with safety requirements.
- **Special Consumer Focus:** Extra safeguards are in place for vulnerable groups, such as children. Keep this product out of reach of children to prevent accidents.
- **EU Contact Point:** For any safety inquiries, ensure you have the relevant contact information for support in your region.
- **Rapid Alerts:** Be aware that updates on unsafe products will be communicated quickly via the Safety Gate system.

## Specific Safety Precautions for Use

- **Installation Safety:** Ensure that the scope base is installed correctly to prevent accidents. Follow installation instructions carefully.
- **Torque Specifications:** Use a torque wrench to apply the recommended torque of 20 in/lbs. Overtightening can damage the scope base or the rifle.
- **Use of Loctite:** A drop of blue Loctite is recommended to secure screws. Ensure that Loctite is applied correctly and allowed to cure as instructed.
- **Compatible Equipment:** Only use Picatinny or Weaver scope rings with this scope base. Using incompatible equipment may result in failure during use.
- **Zeroing the Rifle:** When using a 20 MOA mount, it is recommended to zero the rifle at 200 yards. Adjustments should be made based on shooting distance.
- **Inspection:** Regularly inspect the scope base and mounting hardware for wear and damage. Replace any worn or damaged parts immediately.

## Instructions for Installation and Usage

### 1. Gather Required Tools:

- Torque wrench
- T10 wrench (included)
- Blue Loctite (sold separately)

### 2. Installation Steps:

- Ensure the rifle is unloaded and pointed in a safe direction.
- Align the scope base with the mounting points on the Ruger Precision Rifle (RPR).
- Insert the #840 X 1/4 screws provided with the scope base.
- Using the T10 wrench, tighten the screws to a torque of 20 in/lbs.

- Apply a drop of blue Loctite to the screws to secure them in place.
- Allow the Loctite to cure as per the manufacturer's instructions before using the rifle.

### **3. Usage Instructions:**

- Attach compatible Picatinny or Weaver scope rings to the installed scope base.
- Adjust the scope according to your shooting needs.
- Always check the stability of the scope and base before shooting.

## **Disposal Instructions**

- Dispose of the scope base and any components in accordance with local regulations.
- Do not dispose of in regular household waste. Check for recycling programs or hazardous waste disposal sites in your area.

## **Contact Information for Further Support**

For any further inquiries or support regarding the RUGER PRECISION RIFLE HD SCOPE BASE, please refer to the contact information provided with your purchase or on the manufacturer's website.

Thank you for your attention to these safety guidelines. Enjoy your shooting experience responsibly and safely.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)