

WEATHERBY MARK V TRR (6 LUG BOLT) HD SCOPE BASES - EGW

WEATHERBY MARK V TRR (6 LUG BOLT) HD SCOPE BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

Machined From: Solid 7075 T6 Aircraft Grade Aluminum Finish: Matte Black Only Compatible with Picatinny or Weaver scope rings. Mounting Hardware: #6-48 X 1/4 Screws and T-10 Bit Included Torque Specs: 20 in/lbs Center Spread: 4.280" Overall Length of Mount: 6.670" EGW's Weatherby Mark V TRR (Threat Response Rifle) mount is made specific to the gun and ONLY fits the 6 lug Weatherby MK V TRR. This mount comes with a bevel on both sides of the ejection port, making it ambidextrous. The middle spread is the distance between the two middle holes, center to center, on your receiver. The middle spread on our Weatherby Mark V TRR mount is 4.280". If this spread does not match, you may need our Standard Weatherby Mark V mount. The middle spread for our Standard Mark V mount is 4.485". Please see our separate listing for the Weatherby Mark V if you require the standard mount. All action lengths are available in 0 or 20 MOA. We recommend: 0 MOA - if shooting 0-500 yards 20 MOA - if shooting 500-1000 yards Custom silver anodizing is available upon request, for an additional charge of \$15 (a lead time of approximately 3 months is also associated with this custom anodizing. Please call us if you are interested in placing a custom order). Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount, weighing in at 2-3oz on average. Also, in many cases, it will not obstruct usage of factory iron sights. EGW's one piece scope mounts are the obvious choice for hunters and tactical shooters alike. This mount is a Picatinny-style base and compatible with Picatinny or Weaver scope rings. Add EGW's Practical or HD Scope Rings to make it a complete overhaul! We machine these in our shop using one of our USA-made Fadal machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability. The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is available through our website and is sold separately).



Attributes

- Name: [EGW WEATHERBY MARK V TRR \(6 LUG BOLT\) HD SCOPE BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000602
- Mfr. No.: 80710
- Colour: Matte Black
- Elevation: 0 MOA
- Material: Aluminum
- Model: Mark V
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Weatherby
- Delivery weight: 0.086kg
- Shipping height: 25mm
- Shipping width: 95mm

- Shipping length: 229mm
- UPC: 841370116393

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for WEATHERBY MARK V TRR HD SCOPE BASE
- About Us

Safety Instruction Guide for WEATHERBY MARK V TRR HD SCOPE BASE

Introduction

Thank you for choosing the WEATHERBY MARK V TRR HD SCOPE BASE. This guide provides important safety instructions and information to ensure the proper and safe use of this product. Please read this guide thoroughly before installation and use.

General Safety Guidelines

- Ensure that the product is suitable for your specific firearm model, the Weatherby Mark V TRR (6 Lug Bolt).
- Always handle firearms and firearm accessories with care.
- Store the product in a safe, dry location when not in use.
- Inspect the scope base and mounting hardware for any damage before installation.
- Follow all local laws and regulations regarding firearm accessories.

Specific Safety Precautions for Use

- Use only Picatinny or Weaver scope rings compatible with this scope base.
- Do not exceed the recommended torque specifications of 20 in/lbs during installation.
- Apply a drip of blue Loctite to the screws to prevent loosening during use.
- Ensure that the mount does not obstruct the usage of factory iron sights.
- Be aware of the weight of the mount (approximately 23 oz) and consider the overall weight of your setup.
- If you experience any issues with the installation or functionality of the scope base, cease use immediately and contact support.

Instructions for Installation and Usage

1. Preparation:

- Ensure that your firearm is unloaded and pointed in a safe direction.
- Gather necessary tools: #648 X 1/4 screws, T10 bit, and blue Loctite.

2. Mounting the Scope Base:

- Align the scope base with the receiver of your Weatherby Mark V TRR.
- Check the center spread (4.280") to ensure compatibility.
- Secure the base using the provided screws. Tighten to 20 in/lbs of torque.

3. Installing Scope Rings:

- Attach compatible Picatinny or Weaver scope rings to the rail.
- Adjust the rings to the desired position for optimal eye relief and comfort.

4. Final Checks:

- Inspect the installation to ensure everything is secure.
- Test the functionality of the scope and ensure it is properly aligned.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer usable, consider recycling metal components where possible.

Contact Information for Further Support

For any safety inquiries or additional support regarding the WEATHERBY MARK V TRR HD SCOPE BASE, please refer to the manufacturer's contact information provided with your product packaging.

Conclusion

By following these safety instructions and guidelines, you can ensure a safe and effective experience with your WEATHERBY MARK V TRR HD SCOPE BASE. Always prioritize safety and compliance with local laws when using firearm accessories. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk