

# SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY SCOPE MOUNT - EGW SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This mount was designed for use with the Williams FP-GR TK peep sight. The corresponding front sight and block from Williams are: Lyman Globe Front Sight Williams Rear Sight Top of the receiver to the top of the rear sight dovetail is .330" Top of the receiver to the top of the picatinny rail is .45" This rail is ambidextrous. This mount is milled on both sides for bolt clearance on left or right handed models. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. EGW's one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. They machine these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA.



## Attributes

- Name: [EGW SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000612
- Mfr. No.: 41965
- Colour: Black
- Elevation: 0 MOA
- Material: Aluminum
- Model: Rascal
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Savage Arms
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 102mm
- Shipping length: 229mm
- UPC: 841370113675

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY SCOPE MOUNT
- About Us

# Safety Instruction Guide for SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY SCOPE MOUNT

## Introduction

Thank you for choosing the SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY SCOPE MOUNT by EGW. This guide provides important safety instructions to ensure the safe use and installation of your product. Please read this guide carefully before use.

## General Safety Guidelines

- Ensure that the mount is compatible with your specific firearm model before installation.
- Always handle firearms and accessories with care, following all safety protocols.
- Keep the mount and all related components out of reach of children and unauthorized users.
- Inspect the mount for any damage before installation. Do not use if damaged.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about any recalls or safety notices related to this product through the EU Safety Gate platform.

## Specific Safety Precautions for Use

- Use the mount only for its intended purpose—mounting optics on compatible firearms.
- Ensure that the firearm is unloaded before attempting to install or adjust the mount.
- Use the recommended torque of 20 inch lbs when securing the mount to avoid overtightening, which could damage the firearm or the mount.
- Apply a drop of blue loctite to the mounting screws to prevent loosening during use. (Loctite is sold separately.)
- Avoid obstructing the factory iron sights when installing the mount.
- Always doublecheck that the mount is securely attached before using the firearm.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools, including a torque wrench, loctite, and the provided mounting screws.
- Ensure that the firearm is completely unloaded.

### 2. Mounting the Rail:

- Position the Picatinny rail on the top of the receiver.
- Align the rail with the rear sight dovetail, ensuring that it is level.

### 3. Securing the Mount:

- Insert the mounting screws through the rail into the receiver.
- Handtighten the screws to hold the rail in place.
- Use a torque wrench to apply 20 inch lbs of torque to each screw.
- Apply a drop of blue loctite to each screw to ensure a secure fit.

### 4. Final Checks:

- Verify that the rail is securely mounted and does not move.
- Check for any obstruction of the factory iron sights.

## 5. Using the Mount:

- Attach your scope rings and any other accessories to the Picatinny rail as needed.
- Ensure that all accessories are securely mounted before use.

## Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the mount is damaged beyond repair, dispose of it responsibly, ensuring it does not pose a risk to the environment or public safety.

## Contact Information for Further Support

For any questions or concerns regarding the installation or safety of your SAVAGE RASCAL CUT FOR WILLIAMS SIGHT PICATINNY SCOPE MOUNT, please refer to the manufacturer's contact information provided in the product packaging or visit the manufacturer's website for support.

Thank you for ensuring safe practices while using your new scope mount. Enjoy your shooting experience responsibly!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)