

TAURUS G2, G3, PT709 AND TX22 VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS TAURUS G2/G3 BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with the mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product.



Attributes

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS TAURUS G2/G3 BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000651
- Mfr. No.: 49291
- Colour: Black
- Material: Aluminum
- Model: PT-740,G2S,PT-111,PT-140 G2,TX22,PT-709,G3,G2C
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Taurus
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370117543

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for TAURUS G2, G3, PT709 AND TX22 VORTEX VIPER/VENOM SIGHT MOUNT
- About Us

Safety Instruction Guide for TAURUS G2, G3, PT709 AND TX22 VORTEX VIPER/VENOM SIGHT MOUNT

Introduction

Thank you for choosing the TAURUS G2, G3, PT709 AND TX22 VORTEX VIPER/VENOM SIGHT MOUNT. This product has been designed to enhance your shooting experience. However, it is important to follow safety guidelines to ensure proper usage and to avoid any potential hazards. This guide outlines essential safety instructions, installation procedures, and disposal information in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure that you are familiar with the operation of your firearm before installing this sight mount.
- Always handle firearms with care and treat every firearm as if it is loaded.
- Keep this product out of reach of children and unauthorized users.
- Regularly check for any signs of wear or damage on the sight mount and your firearm.
- Follow all local laws and regulations regarding firearm modifications and usage.
- If you experience any issues with the product, cease use immediately and seek assistance from a qualified gunsmith.

Specific Safety Precautions for Use

- **Installation:** Ensure that the firearm is unloaded before beginning installation.
- **Mounting Hardware:** Use only the provided mounting hardware. Do not substitute with other screws or components.
- **Torque Specifications:** Adhere to the torque specifications (15 in/lbs) when tightening screws to avoid damage.
- **Loctite Application:** Apply blue Loctite to the provided screws to secure the mount but avoid contact with the red dot sight.
- **Qualified Assistance:** If you are unsure about the installation process, consult a qualified gunsmith for assistance.
- **Modification Warning:** Modifying your firearm may void the manufacturer's warranty.

Instructions for Installation and Usage

1. Remove the Rear Sight:

- Ensure the firearm is unloaded.
- Carefully remove the rear sight from your gun.

2. Install the EGW Sight Mount:

- Position the EGW Sight Mount in the dovetail.
- Ensure it is oriented correctly (from left to right with the muzzle facing forward).

3. Tighten Set Screw:

- If applicable, tighten the set screw to secure the mount.

4. Place the Red Dot Sight:

- Position your Vortex Viper/Venom, Burris FastFire, or Docter reddydot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the mount.

5. Apply Loctite:

- Apply blue Loctite to the provided mounting screws before installation.

6. Torque Mounting Screws:

- Use a 5/64" allen wrench to tighten the mounting screws to a torque of 15 in/lbs.

7. Final Check:

- Ensure all screws are tight and the sight mount is securely attached before using your firearm.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic and metal waste.
- Do not dispose of the product in regular household waste.
- Contact your local waste management authority for guidance on proper disposal methods.

Contact Information for Further Support

For any inquiries regarding safety, installation, or product issues, please refer to the contact details provided by the manufacturer or your retailer. It is important to reach out for assistance if you have any concerns regarding the product's safety or functionality.

By following these safety instructions, you can ensure a safe and enjoyable experience with your TAURUS G2, G3, PT709 AND TX22 VORTEX VIPER/VENOM SIGHT MOUNT. Always prioritize safety and seek professional help when needed. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk