

# LPA-LOW VORTEX VIPER/VENOM SIGHT MOUNT - EGW LPA LOW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS BURRIS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. Does not work with Rock Island 1911 or EAA/Tanfoglio Witness with LPA/Bomar style rear sights.



## Attributes

- Name: [EGW LPA LOW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS BURRIS BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000653
- Mfr. No.: 49301
- Colour: Black
- Material: Aluminum
- Model: Witness Elite Match, Baby Desert Eagle, SAR K2P, Jericho 941
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Magnum Research, IWI, EAA
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370115693

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for LPALOW VORTEX VIPER/VENOM SIGHT MOUNT
- About Us

# Safety Instruction Guide for LPALOW VORTEX VIPER/VENOM SIGHT MOUNT

## Introduction

Thank you for choosing the LPALOW VORTEX VIPER/VENOM SIGHT MOUNT. This guide provides important safety information and instructions to ensure proper installation and usage of the product. Please read this guide carefully before use to ensure your safety and the safety of others.

## General Safety Guidelines

- Always follow the manufacturer's instructions for installation and use.
- Ensure that the firearm is unloaded before attempting to install or remove the sight mount.
- Use appropriate tools and equipment when installing the sight mount.
- Inspect the sight mount and hardware for any damage before installation.
- Ensure that the sight mount is securely fastened before using the firearm.
- Do not modify the sight mount or firearm in any way that may affect safety or functionality.
- Keep the sight mount and all accessories out of reach of children and unauthorized users.
- Report any unsafe products or accidents to the relevant authorities.

## Specific Safety Precautions for Use

- This product is designed for use with specific models: Vortex Viper/Venom, Burris FastFire, and Docter reddot sights.
- The sight mount is not compatible with Rock Island 1911 or EAA/Tanfoglio Witness firearms with LPA/Bomar style rear sights.
- Modification of your firearm may void the manufacturer's warranty.
- It is recommended that installation and adjustments be performed by a qualified gunsmith to ensure safety and compliance.
- Use caution when applying blue Loctite to the screws, as excess adhesive can interfere with the sight's function.
- Ensure that the mounting screws are torqued to the specified 15 in/lbs to avoid loosening during use.

## Instructions for Installation and Usage

### 1. Remove the Rear Sight

- Ensure the firearm is unloaded.
- Carefully remove the rear sight from your firearm.

### 2. Install the EGW Sight Mount

- Place the EGW Sight Mount in the dovetail.
- Ensure that the mount is oriented correctly (from left to right with the muzzle facing forward).

### 3. Secure the Mount

- Tighten the set screw (if applicable) to secure the mount in place.

### 4. Attach the Red Dot Sight

- Place the red dot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the mount.

## 5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws.

## 6. Torque Mounting Screws

- Use a 5/64" allen wrench to torque the mounting screws to 15 in/lbs.

## 7. Final Check

- Ensure that all components are secure and that the sight is properly aligned before using the firearm.

## Disposal Instructions

- Dispose of packaging materials and any unused components in accordance with local regulations.
- Do not dispose of the product in household waste. Check for local recycling programs or hazardous waste disposal options.

## Contact Information for Further Support

For any questions or concerns regarding the installation or use of the LPALOW VORTEX VIPER/VENOM SIGHT MOUNT, please contact the manufacturer or a qualified gunsmith for assistance.

Thank you for prioritizing safety and compliance with these guidelines. Enjoy your shooting experience responsibly.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)