

# **WALTHER 22 VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS WALTHER 1911-22 BLK**

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. No alterations are required. You can take the mount off and replace your rear sight at any time. Mounting hardware included.

Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product.



## **Attributes**

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS WALTHER 1911-22 BLK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000654
- Mfr. No.: 49302
- Colour: Black
- Material: Aluminum
- Model: P22
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Walther
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370115709

## **Item details**

Made in USA

# Table of Contents

- Startpage
- WALther 22 VORTEX VIPER/VENOM SIGHT MOUNT SAFETY INSTRUCTIONS
- About Us

# WALTHER 22 VORTEX VIPER/VENOM SIGHT MOUNT SAFETY INSTRUCTIONS

## Introduction

Thank you for choosing the WALTHER 22 Vortex Viper/Venom Sight Mount. This guide provides essential safety instructions to ensure the proper use and installation of your product. Please read this manual carefully before using the sight mount.

## General Safety Guidelines

- Ensure the product is suitable for your firearm model before installation.
- Always handle firearms responsibly and in accordance with local laws and regulations.
- Keep the sight mount and all associated tools out of reach of children and unauthorized users.
- Inspect the sight mount regularly for any signs of wear or damage.
- Do not use the sight mount if it has been modified or damaged.
- Report any unsafe products or accidents to the appropriate authorities.

## Specific Safety Precautions for Use

- Ensure the firearm is unloaded before installing the sight mount.
- Use only the recommended tools for installation to prevent damage.
- Apply blue Loctite only to the provided mounting screws to ensure a secure fit.
- Avoid placing any foreign objects between the sight mount and the firearm.
- If you are unsure about the installation process, consult a qualified gunsmith.

## Instructions for Installation and Usage

### 1. Remove the Rear Sight

- Carefully remove the existing rear sight from your firearm.

### 2. Install the EGW Sight Mount

- Align the EGW Sight Mount in the dovetail from left to right with the muzzle facing forward.

### 3. Tighten Set Screw (if applicable)

- Use the appropriate tool to tighten the set screw securely.

### 4. Place the Red Dot Sight

- Position your Vortex Viper/Venom, Burris FastFire, or Docter reddot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the sight mount.

### 5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to ensure they remain secure during use.

### 6. Torque Mounting Screws

- Use a torque wrench to tighten the mounting screws to 15 in/lbs.

### 7. Check Installation

- After installation, ensure all screws are tightly secured and the sight is properly aligned.

## **Disposal Instructions**

- Dispose of the sight mount and any packaging materials in accordance with local regulations.
- Do not dispose of the product in household waste. Check for local recycling programs that accept metal and plastic materials.

## **Contact Information for Further Support**

For any questions or concerns regarding the installation or use of your WALTHER 22 Vortex Viper/Venom Sight Mount, please consult a qualified gunsmith or contact the manufacturer directly.

By following these safety instructions, you can ensure the proper use and longevity of your WALTHER 22 Vortex Viper/Venom Sight Mount. Always prioritize safety and responsible firearm handling. Thank you for your attention to these important guidelines.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)