

H&K USP VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS H&K USP BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This mount does not work with USP Compact, USP Expert, USP Elite, VP9, VP40, P30, P30L, P30SK, HK45, or HK45C.



Attributes

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS H&K USP BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000657
- Mfr. No.: 49305
- Colour: Black
- Material: Aluminum
- Model: USP 9,USP Tactical 45,USP Tactical 9mm,USP 40,USP 45
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Heckler & Koch
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370114214

Item details

Made in USA

Table of Contents

- Startpage
- H&K USP Vortex Viper/Venom Sight Mount Safety Instructions
- About Us

H&K USP Vortex Viper/Venom Sight Mount Safety Instructions

Introduction

Thank you for choosing the H&K USP Vortex Viper/Venom Sight Mount. This guide provides essential safety instructions and installation guidelines to ensure the proper and safe use of this product. Please read all instructions carefully before installation and use.

General Safety Guidelines

- Ensure that the firearm is unloaded before attempting to install or remove the sight mount.
- Always handle firearms with care and follow all applicable safety rules.
- This sight mount is designed for use with specific models of the H&K USP series. Ensure compatibility before installation.
- Modification of your firearm may nullify the manufacturer's warranty.
- If you are unsure about installation, consult a qualified gunsmith.
- Keep this product out of reach of children and unauthorized users.
- Report any unsafe product conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Ensure the sight mount is securely attached to avoid any accidents during use.
- Use the provided mounting hardware only; do not substitute with other screws or fasteners.
- Avoid using excessive force when tightening screws to prevent damage to the sight mount or firearm.
- If any part of the sight mount appears damaged or worn, discontinue use immediately and consult a professional.
- This mount is not compatible with USP Compact, USP Expert, USP Elite, VP9, VP40, P30, P30L, P30SK, HK45, or HK45C. Using it with these models may lead to safety hazards.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Ensure your firearm is unloaded.
- Carefully remove the rear sight from your H&K USP.

2. Install the EGW Sight Mount

- Position the EGW Sight Mount in the dovetail of your firearm.
- Ensure the mount is oriented from left to right with the muzzle facing forward.

3. Tighten the Set Screw

- If applicable, tighten the set screw securely to hold the mount in place.

4. Attach the Red Dot Sight

- Place your Vortex Viper/Venom, Burris FastFire, or Docter red dot sight onto the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the mount to keep Loctite off the sight.

5. Apply Loctite

- Apply blue Loctite to the provided mounting screws to secure the red dot sight.

6. Torque the Mounting Screws

- Tighten the mounting screws to 15 in/lbs using a 5/64" allen wrench.

7. Check Installation

- After installation, doublecheck that all screws are tight and the sight is secure before using the firearm.

Disposal Instructions

- Dispose of packaging materials and any unused components in accordance with local regulations.
- Do not dispose of this product in household waste. Consult local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the installation or use of the H&K USP Vortex Viper/Venom Sight Mount, please consult a qualified gunsmith or contact the manufacturer directly for assistance.

By following these safety instructions, you can ensure a safe and effective installation of the H&K USP Vortex Viper/Venom Sight Mount. Thank you for your attention to safety and proper usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk