

S&W M&P VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS S&W M&P BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This Mount does not fit: Smith & Wesson M&P C.O.R.E Series (Already optics ready) Smith & Wesson M&P Shield EZ .380 Smith & Wesson M&P .22 Compact Smith & Wesson SW9VE Smith & Wesson SW40VE



Attributes

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS S&W M&P BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000660
- Mfr. No.: 49308
- Colour: Black
- Material: Aluminum
- Model: M&P Compact,M&P Shield,SD9-VE,M&P 2.0 Compact
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Smith & Wesson
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370113934

Item details

Made in USA

Table of Contents

- Startpage
- Consumer Safety Instruction Guide for S&W M&P Vortex Viper/Venom Sight Mount
- About Us

Consumer Safety Instruction Guide for S&W M&P Vortex Viper/Venom Sight Mount

Introduction

Thank you for choosing the S&W M&P Vortex Viper/Venom Sight Mount. This guide provides essential safety instructions and installation guidelines to ensure the safe use of this product. Please read this guide thoroughly before installation and use.

General Safety Guidelines

- Ensure the product is installed by a qualified gunsmith to avoid any hazards.
- Always follow the manufacturer's instructions for installation and use.
- Regularly check the sight mount for any signs of wear or damage.
- Keep this product out of reach of children and vulnerable individuals.
- Report any unsafe products or incidents to the appropriate authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- This sight mount is designed for specific models of Smith & Wesson firearms. Ensure compatibility before installation.
- Do not modify the sight mount or firearm, as this may void the warranty and create safety risks.
- Use only the provided mounting hardware to ensure proper installation.
- Apply blue Loctite to screws to prevent loosening but avoid contact with the red dot sight.
- Always torque mounting screws to the specified 15 in/lbs to ensure secure attachment.
- If you experience any issues during installation or use, stop immediately and consult a qualified gunsmith.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully take off the existing rear sight from your firearm.

2. Install the EGW Sight Mount

- Position the EGW Sight Mount in the dovetail from left to right (with the muzzle facing forward).
- Ensure it is seated properly in the dovetail.

3. Tighten Set Screw (if applicable)

- If your mount has a set screw, tighten it securely.

4. Attach the Red Dot Sight

- Place your Vortex Viper/Venom, Burris FastFire, or Docter reddot sight onto the EGW Sight Mount.
- To facilitate easier removal, place a small piece of paper between the red dot sight and the mount.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws before installation.

6. Torque Mounting Screws

- Use a 5/64" allen wrench to torque the mounting screws to 15 in/lbs.

7. Final Check

- Inspect the installation to ensure everything is secure and properly aligned.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the product is damaged or no longer in use, follow local guidelines for disposal of electronic and metal components.

Contact Information for Further Support

For any inquiries or support regarding the S&W M&P Vortex Viper/Venom Sight Mount, please consult with a qualified gunsmith or contact the manufacturer directly.

By following these guidelines, you can ensure the safe and effective use of your S&W M&P Vortex Viper/Venom Sight Mount. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk