

# OVERSIZED NOVAK 0.007" VORTEX VIPER/VENOM SIGHT MOUNT - EGW OVERSIZED NOVAK CUT SIGHT MOUNT FOR VORTEX VIPER/VENOM BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

This mount is NOT a drop in part and will require fitting. EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. EGW products should be installed and checked by a qualified and competent gunsmith. Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail after checking for fit Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This mount fits: Firearms with oversized Novak cut dovetails. This mount is made .007"" larger than a standard Novak cut and will require fitting.



## Attributes

- Name: [EGW OVERSIZED NOVAK CUT SIGHT MOUNT FOR VORTEX VIPER/VENOM BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000661
- Mfr. No.: 49311-OS
- Colour: Black
- Material: Aluminum
- Number of Bases: 1-Piece
- Style: Tactical
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370112029

## Item details

Made in USA

# Table of Contents

- Startpage
- OVERSIZED NOVAK 0.007" VORTEX VIPER/VENOM SIGHT MOUNT SAFETY INSTRUCTIONS
- About Us

# OVERSIZED NOVAK 0.007" VORTEX VIPER/VENOM SIGHT MOUNT SAFETY INSTRUCTIONS

## Introduction

Thank you for purchasing the OVERSIZED NOVAK 0.007" VORTEX VIPER/VENOM SIGHT MOUNT. This guide provides essential safety instructions and installation guidelines to ensure the safe use of this product. Please read this manual thoroughly before installation and use.

## General Safety Guidelines

- Ensure the mount is installed by a qualified gunsmith to avoid potential hazards.
- This product is not a dropin part and will require fitting. Improper installation may lead to firearm malfunction or injury.
- Always handle firearms safely and responsibly, following all local laws and regulations.
- Keep this product out of reach of children and vulnerable individuals.
- Regularly check the mounting hardware for tightness and integrity before use.

## Specific Safety Precautions for Use

- Always install the EGW sight mount from the left to the right with the muzzle facing forward.
- Use a small piece of paper between the red dot sight and the sight mount during installation for easier removal and to keep Loctite off the red dot sight.
- Apply blue Loctite to the provided mounting screws to ensure secure installation.
- Do not modify your firearm in a way that may void the manufacturer's warranty.
- Be aware that modification of your firearm may lead to liability issues in case of accidents or injuries.

## Instructions for Installation and Usage

### 1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm.

### 2. Install the EGW Sight Mount

- Check for fit before installation.
- Place the EGW Sight Mount in the dovetail.

### 3. Tighten Set Screw

- If applicable, tighten the set screw securely.

### 4. Position the Red Dot Sight

- Place the red dot sight on the EGW Sight Mount. Use a small piece of paper between the two for easier removal.

### 5. Apply Loctite

- Apply blue Loctite to the provided mounting screws.

### 6. Torque Mounting Screws

- Torque the mounting screws to 15 in/lbs.

## 7. Use the Correct Screws

- Use the 2 Button Head Cap Screws for Vortex Viper and Venom Sights.
- Use the 2 Flat Head Cap Screws for Burris FastFire and Docter Sights.

## 8. Use Appropriate Tools

- The screws included with this mount require a 5/64" allen wrench for installation.

## Disposal Instructions

- Dispose of packaging materials and any unused parts responsibly, following local waste disposal regulations.
- If the product is no longer needed, please dispose of it in accordance with local electronic waste disposal guidelines.

## Contact Information for Further Support

For further support or inquiries regarding safety, installation, or product issues, please contact the manufacturer or a qualified gunsmith.

Please ensure you adhere to these safety instructions to ensure a safe and effective use of your OVERSIZED NOVAK 0.007" VORTEX VIPER/VENOM SIGHT MOUNT. Your safety is our priority.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)