

KIMBER 1911 ADJUSTABLE SIGHT VORTEX VIPER/VENOM SIGHT MOUNT - EGW ADJ SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS KIMBER 1911 BLK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. This mount fits: Kimber 1911 (adjustable rear sights for windage and elevation) Ruger SR1911 (adjustable rear sights for windage and elevation)



Attributes

- Name: [EGW ADJ SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS KIMBER 1911 BLK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000663
- Mfr. No.: 49316
- Colour: Black
- Material: Aluminum
- Model: 1911,SR1911
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Ruger,Kimber
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370112906

Item details

Made in USA

Table of Contents

- Startpage
- KIMBER 1911 Adjustable Sight Vortex Viper/Venom Sight Mount Safety Instructions
- About Us

KIMBER 1911 Adjustable Sight Vortex Viper/Venom Sight Mount Safety Instructions

Introduction

Thank you for choosing the KIMBER 1911 Adjustable Sight Vortex Viper/Venom Sight Mount. This product is designed to enhance your shooting experience by allowing the mounting of red dot sights securely on your firearm. Please read this safety instruction guide carefully to ensure proper use and to maintain your safety and the safety of others.

General Safety Guidelines

- Always handle your firearm responsibly and in accordance with local laws and regulations.
- Ensure that the firearm is unloaded before installing or adjusting the sight mount.
- Be aware of your surroundings and ensure that the area is safe before handling your firearm.
- Store the sight mount and your firearm in a secure location, away from children and unauthorized users.
- Regularly check the sight mount and screws for wear and tear or damage.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Only use the sight mount with compatible red dot sights, such as Vortex Viper/Venom, Burris FastFire, or Docter.
- Ensure that the mounting hardware is securely tightened before use to avoid any accidents during operation.
- Do not modify the sight mount or use it in a way not intended by the manufacturer.
- If you experience any issues during installation or use, discontinue use and consult a qualified professional.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Start by carefully removing the rear sight from your Kimber 1911.

2. Install the EGW Sight Mount

- Align the EGW Sight Mount in the dovetail, ensuring it is positioned from left to right with the muzzle facing forward.

3. Secure the Mount

- Tighten the set screw (if applicable) to ensure the mount is secure.

4. Place the Red Dot Sight

- Position the red dot sight on the EGW Sight Mount. For easier removal and to protect the sight, place a small piece of paper between the red dot sight and the mount.

5. Apply Loctite

- Apply blue Loctite to the provided mounting screws to prevent loosening due to recoil.

6. Torque the Screws

- Torque the mounting screws to 15 in/lbs using the appropriate tools. Note that:
 - 2 Button Head Cap Screws are provided for Vortex Viper and Venom Sights.
 - 2 Flat Head Cap Screws are provided for Burris FastFire and Docter Sights.

7. Use the Correct Tools

- The screws included with this mount require a 5/64" allen wrench for installation.

Disposal Instructions

- Dispose of any packaging materials responsibly.
- If the sight mount becomes damaged beyond repair, please follow local regulations for the disposal of metal components.
- Do not dispose of the sight mount in regular household waste if it contains any hazardous materials.

Contact Information for Further Support

For any inquiries regarding this product, please refer to the manufacturer's contact information provided with your purchase. Ensure you have the product details handy for efficient assistance.

By following these safety instructions, you can ensure a safe and enjoyable experience with your KIMBER 1911 Adjustable Sight Vortex Viper/Venom Sight Mount. Always prioritize safety and responsible handling of your firearm.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk