

SIG SAUER P220-229, 320 VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS SIG P220-229/320 BLK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

This mount does not work on any optics ready Sigs. EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This mount does not fit: Sig 1911s Any Optics Ready Sigs i.e. P226 Legion RX, P229 RX, P320 X-Carry etc. P210 Target P365 (The dovetail cut is too deep to work with our mount) FN 509 Tactical



Attributes

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS SIG P220-229/320 BLK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000665
- Mfr. No.: 49318
- Colour: Black
- Material: Aluminum
- Model: P210A,P220,Thunder HC,P226,P227,P938,M11-A1,SP2022,P225,P239,Thunder UC,P229,P320,P224,509,P245,MK25,P228,P238
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: FN,Sig Sauer,Bersa
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370112920

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SIG SAUER P220229, 320 Vortex Viper/Venom Sight Mount
- About Us

Safety Instruction Guide for SIG SAUER P220229, 320 Vortex Viper/Venom Sight Mount

Introduction

Thank you for choosing the SIG SAUER P220229, 320 Vortex Viper/Venom Sight Mount. This guide provides essential safety instructions and installation guidelines to ensure your product is used safely and effectively. Please read this document carefully before using the product.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Always inspect the product for any damage before installation and use.
- Only use the mount with compatible sights as specified in the product description.
- Keep this product out of reach of children and unauthorized users.
- If you experience any issues or have questions, consult a qualified gunsmith or contact customer support.

Specific Safety Precautions for Use

- This mount does not work on any opticsready Sig models.
- Ensure the muzzle is facing forward during installation.
- Do not attempt to modify the mount or your firearm in a way that could compromise safety.
- The installation should be performed by a qualified gunsmith to avoid potential damage or injury.
- Use caution when handling tools and components during installation.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm.

2. Install the EGW Sight Mount

- Install the EGW Sight Mount in the dovetail, ensuring it is aligned correctly.

3. Tighten Set Screw

- If applicable, tighten the set screw to secure the mount in place.

4. Place the Red Dot Sight

- Position the red dot sight on the EGW Sight Mount. For easier removal, place a small piece of paper between the red dot sight and the mount to keep Loctite off the sight.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to prevent loosening.

6. Torque Mounting Screws

- Torque the mounting screws to 15 in/lbs.
- Use the following screws as needed:
 - 2 Button Head Cap Screws Provided for Vortex Viper and Venom Sights
 - 2 Flat Head Cap Screws Provided for Burris FastFire and Docter Sights

- The screws require a 5/64" allen wrench for installation.

Disposal Instructions

- Dispose of the product and any packaging materials in accordance with local regulations.
- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For any inquiries or concerns regarding the SIG SAUER P220229, 320 Vortex Viper/Venom Sight Mount, please consult a qualified gunsmith or reach out to the manufacturer's customer support.

Compliance with EU General Product Safety Regulation (GPSR)

This product complies with the EU GPSR, ensuring that: * It is safe for use and does not pose any unaddressed risks. * There are standardized recall notices and remedies available for dangerous products. * Online shopping provides the same safety protections as physical stores. * Extra safeguards are in place for vulnerable groups. * An EUbased contact is available for safety inquiries. * Rapid alerts on unsafe products are communicated through the Safety Gate system.

Reporting Unsafe Products

- If you encounter an unsafe product or experience an accident, please report it to the appropriate authorities.
- Stay informed about recall updates on the EU's Safety Gate platform.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priorities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk