

SPRINGFIELD XD, XDM VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS SPRINGFIELD XD BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. Does not fit: Springfield XD(M)® 5.25"" COMPETITION SERIES MODEL Any Optics Ready Springfield XD



Attributes

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS SPRINGFIELD XD BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000669
- Mfr. No.: 49323
- Colour: Black
- Material: Aluminum
- Model: XD-E,XD-M,XDS,XD Mod 2,XD,XD-Subcompact
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Springfield
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370112975

Item details

Made in USA

Table of Contents

- Startpage
- SPRINGFIELD XD, XDM VORTEX VIPER/VENOM SIGHT MOUNT SAFETY INSTRUCTIONS
- About Us

SPRINGFIELD XD, XDM VORTEX VIPER/VENOM SIGHT MOUNT SAFETY INSTRUCTIONS

Introduction

Thank you for purchasing the Springfield XD, XDM Vortex Viper/Venom Sight Mount. This guide provides essential safety instructions and installation guidelines to ensure safe and effective use of the product. Please read all instructions carefully before installation and use.

General Safety Guidelines

- Ensure that the product is compatible with your firearm model before installation.
- Always handle firearms with care and follow all safety procedures.
- Keep all components out of reach of children and unauthorized users.
- Use the product only for its intended purpose as described in this manual.
- Regularly inspect the mount and sight for any signs of wear or damage.
- If you experience any issues during installation or use, consult a qualified gunsmith.

Specific Safety Precautions for Use

- Do not modify the mount or your firearm in a way that could compromise safety or functionality.
- Only use the mounting hardware provided with the product. Using other hardware may lead to improper installation and potential hazards.
- When installing the sight mount, ensure that the firearm is unloaded and pointed in a safe direction.
- If you are unsure about the installation process, seek assistance from a qualified gunsmith.
- Ensure that the red dot sight is securely mounted before using the firearm. Loose components can lead to misalignment and unsafe conditions.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the rear sight from your firearm.

2. Install the EGW Sight Mount

- Insert the EGW Sight Mount into the dovetail from left to right (with the muzzle facing forward).
- Ensure the mount is properly seated in the dovetail.

3. Tighten the Set Screw

- If applicable, tighten the set screw to secure the mount in place.

4. Place the Red Dot Sight

- Position the red dot sight on the EGW Sight Mount.
- To facilitate easier removal and protect the sight, place a small piece of paper between the red dot sight and the mount.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to prevent loosening over time.

6. Torque Mounting Screws

- Torque the mounting screws to 15 in/lbs.
- Use the following screws as appropriate:
 - 2 Button Head Cap Screws for Vortex Viper and Venom Sights
 - 2 Flat Head Cap Screws for Burris FastFire and Docter Sights
- A 5/64" allen wrench is required for installation.

7. Check Installation

- After installation, doublecheck that all screws are tightened and the sight is securely mounted.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the product is no longer in use, dispose of it responsibly. Check local regulations for proper disposal methods of firearm accessories.

Contact Information for Further Support

For any questions or concerns regarding the installation or safety of this product, please consult a qualified gunsmith or refer to the manufacturer's website for additional resources.

Important Note: Modification of your firearm may void the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. The manufacturer assumes no liability for damage or injury resulting from improper installation or use of this product.

Final Reminder

Always prioritize safety when handling firearms and accessories. Regularly review these safety instructions to ensure proper use and maintenance of your Springfield XD, XDM Vortex/Venom Sight Mount.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk