

H&K USP LEUPOLD DELTAPOINT PRO SIGHT MOUNT - EGW H&K USP LEUPOLD DELTAPOINT PRO SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Leupold DeltaPoint Pro, JPoint, Redfield Accelerator, or Optima red-dot sight. No alterations are required. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This mount does not fit: USP Compact (rear sight cut depth is .200"" instead of .160"") USP Expert USP Elite VP9 VP40 P30 P30L P30SK HK45 HK45C



Attributes

- Name: [EGW H&K USP LEUPOLD DELTAPOINT PRO SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000681
- Mfr. No.: 49406
- Colour: Black
- Material: Aluminum
- Model: USP Tactical 9mm, USP Tactical 45, USP 9, USP 40, USP 45
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Heckler & Koch
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370114245

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for H&K USP Leupold DeltaPoint Pro Sight Mount
- About Us

Safety Instruction Guide for H&K USP Leupold DeltaPoint Pro Sight Mount

Introduction

Thank you for choosing the H&K USP Leupold DeltaPoint Pro Sight Mount. This guide provides essential safety instructions and installation guidelines to ensure the safe and effective use of your product. Please read this manual carefully before installation and use.

General Safety Guidelines

- Always handle firearms and accessories with care and responsibility.
- Ensure that the firearm is unloaded before beginning installation or maintenance.
- Follow all local laws and regulations regarding firearm modifications and accessories.
- Ensure that the product is used only for its intended purpose.
- Be aware of potential hazards associated with the installation and use of this product.
- Keep this product out of reach of children and unauthorized users.
- If you have any doubts about the installation process, consult a qualified gunsmith.

Specific Safety Precautions for Use

- This mount is designed for specific models of the H&K USP series. Ensure compatibility before installation.
- Modification of your firearm may void the manufacturer's warranty. Consult a qualified gunsmith if unsure.
- Improper installation may lead to damage or injury. Follow the installation instructions carefully.
- Do not exceed the recommended torque specifications when securing the mounting screws.
- Use blue Loctite on the screws to prevent loosening, but avoid contact with the red dot sight.
- If you notice any unusual behavior or damage to the product, discontinue use immediately and seek assistance.

Instructions for Installation and Usage

1. **Remove the rear sight** from your H&K USP firearm.
2. **Install the EGW Sight Mount** in the dovetail, ensuring it is aligned correctly.
3. **Tighten the set screw** (if applicable) to secure the mount.
4. **Place the red dot sight** on the EGW Sight Mount. To facilitate future removal, place a small piece of paper between the red dot sight and the mount.
5. **Apply blue Loctite** to the provided mounting screws to secure the red dot sight.
6. **Torque the mounting screws** to 15 in/lbs to ensure a tight fit.
7. **Check the installation** to ensure the mount is secure and the sight is properly aligned before use.

Disposal Instructions

- Dispose of packaging materials and any unused parts according to local regulations.
- Do not dispose of the product in regular household waste. Check for local recycling programs or hazardous waste disposal options.

Contact Information for Further Support

For any inquiries regarding the safety or functionality of this product, please contact the manufacturer or a qualified gunsmith.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priorities.
Enjoy your shooting experience with the H&K USP Leupold DeltaPoint Pro Sight Mount.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk