

EAA SUPER SIGHT LEUPOLD DELTAPOINT PRO SIGHT MOUNT - EGW

EAA SUPER SIGHT MOUNT FOR LEUPOLD DELTA POINT PRO BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Leupold DeltaPoint Pro, JPoint, Redfield Accelerator, or Optima red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This mount fits: Elite Stock II with adjustable (LPA/Bomar style, shown above) rear sight Elite Stock III with adjustable (LPA/Bomar style, shown above) rear sight Hunter with adjustable (LPA/Bomar style, shown above) rear sight Limited Custom with adjustable (LPA/Bomar style, shown above) rear sight Limited Custom Xtreme with adjustable (LPA/Bomar style, shown above) rear sight Match Elite with adjustable (LPA/Bomar style, shown above) rear sight Match Xtreme with adjustable (LPA/Bomar style, shown above) rear sight P Match with adjustable (LPA/Bomar style, shown above) rear sight P Match Pro with adjustable (LPA/Bomar style, shown above) rear sight Stock II Xtreme with adjustable (LPA/Bomar style, shown above) rear sight Stock III Xtreme with adjustable (LPA/Bomar style, shown above) rear sight This mount does not fit: EAA / Tanfoglio Witness with fixed rear sight EAA / Tanfoglio Witness with Novak style adjustable rear sight, shown above



Attributes

- Name: [EGW EAA SUPER SIGHT MOUNT FOR LEUPOLD DELTA POINT PRO BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000682
- Mfr. No.: 49407
- Colour: Black
- Material: Aluminum
- Model: P Match, Hunter, Stock II Xtreme, Elite Stock II, Limite Custom Xtreme, P Match Pro
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: EAA
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370114238

Item details

Made in USA

Table of Contents

- Startpage
- EAA SUPER SIGHT LEUPOLD DELTAPOINT PRO SIGHT MOUNT Safety Instruction Guide
- About Us

EAA SUPER SIGHT LEUPOLD DELTAPOINT PRO SIGHT MOUNT Safety Instruction Guide

Introduction

Thank you for choosing the EAA SUPER SIGHT LEUPOLD DELTAPOINT PRO SIGHT MOUNT. This guide provides essential safety information, installation instructions, and guidelines for proper use to ensure your safety and the longevity of your product. Please read this guide carefully before use.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Always handle firearms and related accessories with care.
- Inspect the product for any damage before installation.
- Do not modify the product in any way, as this may void the warranty and pose safety risks.
- Store the product in a safe place, away from children and unauthorized users.
- Report any unsafe products or accidents to the relevant authorities.
- Regularly check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Use the product only with compatible firearms as listed in the product description.
- Ensure that the firearm is unloaded before installing or removing the sight mount.
- Avoid using the product in adverse weather conditions that may affect visibility or handling.
- Do not exceed the recommended torque settings when installing the sight mount to prevent damage.
- If unsure about installation or use, consult a qualified gunsmith.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Carefully remove the existing rear sight from your firearm.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount in the dovetail from the left to the right, ensuring the muzzle is facing forward.
- Tighten the set screw (if applicable) to secure the mount in place.

3. Attach the Red Dot Sight

- Place your red dot sight on the EGW Sight Mount.
- For easier removal and to protect the sight, place a small piece of paper between the red dot sight and the mount.

4. Apply Loctite

- Apply blue Loctite to the provided mounting screws to secure the sight.

5. Torque the Mounting Screws

- Torque the mounting screws to 15 in/lbs to ensure a secure fit.

6. Final Check

- After installation, doublecheck that all screws are tightened and the sight is securely mounted.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Check with local waste management authorities for proper disposal methods.

Contact Information for Further Support

- For safety inquiries and further assistance, please reach out to your local distributor or retailer.

Thank you for your attention to these safety guidelines. Proper installation and usage will enhance your shooting experience while ensuring your safety and the safety of others.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk