

H&K VP9, P30, HK45, VP40 LEUPOLD DELTAPOINT PRO SIGHT MOUNT - EGW H&K VP9, P30, HK45, VP40 LEUPOLD DELTAPOINT PRO SIGHT MNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Leupold DeltaPoint Pro, JPoint, Redfield Accelerator, or Optima red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. This mount is not intended for use with the optics ready version of these pistols. This mount does not fit: HK USP



Attributes

- Name: [EGW H&K VP9, P30, HK45, VP40 LEUPOLD DELTAPOINT PRO SIGHT MNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000683
- Mfr. No.: 49408
- Colour: Black
- Material: Aluminum
- Model: P30L,45,P30,45C,VP9SK,VP9,VP40,P30sk
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Heckler & Koch
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370114221

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for H&K VP9, P30, HK45, VP40 LEUPOLD DELTAPOINT PRO SIGHT MOUNT
- About Us

Safety Instruction Guide for H&K VP9, P30, HK45, VP40 LEUPOLD DELTAPOINT PRO SIGHT MOUNT

Introduction

Thank you for choosing the EGW Sight Mount for your H&K VP9, P30, HK45, and VP40 pistols. This guide provides essential safety instructions and installation guidelines to ensure the safe use of your product in compliance with the EU General Product Safety Regulation (GPSR). Please read this guide thoroughly before installation and usage.

General Safety Guidelines

- Ensure safe use of the EGW Sight Mount by following all instructions carefully.
- Always handle firearms responsibly and in accordance with local laws and regulations.
- Be aware of potential hazards associated with the installation and use of the sight mount.
- This product is not intended for use with the opticsready version of these pistols.
- Modification of your firearm may void the manufacturer's warranty.
- This product should be installed and checked by a qualified gunsmith.

Specific Safety Precautions for Use

- The sight mount is designed to be installed from the left to the right, with the muzzle facing forward.
- Always ensure the firearm is unloaded before beginning installation.
- Use caution when removing the rear sight and installing the EGW Sight Mount to avoid injury.
- When placing the red dot sight on the EGW Sight Mount, consider using a small piece of paper between the sight and the mount to facilitate easier removal and protect the sight from Loctite.
- Apply blue Loctite to the provided mounting screws to secure the sight properly.
- Torque the mounting screws to 15 in/lbs to prevent loosening during use.
- Be aware that improper installation or use of this product may result in damage or injury.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Ensure the firearm is unloaded.
- Carefully remove the rear sight from your gun.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount into the dovetail from the left to the right.
- Ensure the mount is seated properly.

3. Tighten the Set Screw

- If applicable, tighten the set screw on the mount to secure it in place.

4. Place the Red Dot Sight

- Position your Leupold DeltaPoint Pro, JPoint, Redfield Accelerator, or Optima reddot sight onto the EGW Sight Mount.
- (Optional) Place a small piece of paper between the red dot sight and the mount to assist with

future removal.

5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to secure the red dot sight.

6. Torque Mounting Screws

- Use a torque wrench to tighten the mounting screws to 15 in/lbs.

7. Check Installation

- Verify that everything is securely fastened before using your firearm.

Disposal Instructions

- Dispose of any packaging materials in accordance with local recycling regulations.
- Do not dispose of the product in regular household waste.
- Check local guidelines for the proper disposal of firearm accessories.

Contact Information for Further Support

For any questions or concerns regarding the installation and use of the EGW Sight Mount, please consult a qualified gunsmith or contact the manufacturer directly for assistance.

Please remember to report any unsafe products or accidents to the appropriate authorities and to check for recall updates on the EU's Safety Gate platform. Your safety is our priority, and we encourage responsible use of all firearms and accessories.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk