

# **S&W K, L, N, X FRAME REVOLVERS VORTEX RAZOR SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX RAZOR FITS S&W K, L, N, X FRAME BLACK**

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Razor, C-More RTS or STS red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs The screws that are included with this mount require a 5/64" allen wrench for installation. This mount fits: Smith & Wesson K Frame Revolvers Smith & Wesson L Frame Revolvers Smith & Wesson N Frame Revolvers Smith & Wesson X Frame Revolvers If your revolver is not drilled and tapped this mount will not work. The best way to verify that it is/is not drilled and tapped is to open the cylinder and check the rib underneath. There should be through holes that are drilled and tapped. If there are not (like the above image) this mount will not work without you having the gun drilled and tapped. You can have a competent and qualified gunsmith drill and tap the top strap with the standard S&W hole pattern which will allow you to use our mount.



## **Attributes**

- Name: [EGW SIGHT MOUNT FOR VORTEX RAZOR FITS S&W K, L, N, X FRAME BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000691
- Mfr. No.: 49438
- Colour: Black
- Material: Aluminum
- Model: N Frame,K Frame,X Frame,L Frame
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Smith & Wesson
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370113019

## **Item details**

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for S&W K, L, N, X Frame Revolvers Vortex Razor Sight Mount
- About Us

# Safety Instruction Guide for S&W K, L, N, X Frame Revolvers Vortex Razor Sight Mount

## Introduction

Thank you for choosing the S&W K, L, N, X Frame Revolvers Vortex Razor Sight Mount by EGW. This guide provides essential safety information and instructions to ensure safe and effective use of the product. Please read this guide carefully before installation and use.

## General Safety Guidelines

- Ensure the product is compatible with your firearm. This mount is designed specifically for Smith & Wesson K, L, N, and X Frame revolvers.
- Always handle firearms safely and responsibly. Follow all local laws and regulations regarding firearm usage.
- Store the sight mount in a secure location when not in use to prevent unauthorized access, especially by children.
- Regularly inspect the mount and sight for signs of wear or damage. If any issues are found, do not use the product until it has been repaired or replaced.
- Be aware of your surroundings when using firearms equipped with this mount and sight. Always ensure a safe backdrop and target area.

## Specific Safety Precautions for Use

- **Age Restriction:** This product is intended for use by individuals who are at least 18 years old. Ensure that minors are supervised by a qualified adult when handling firearms.
- **Installation Safety:** Only install the mount when the firearm is unloaded. Always doublecheck that the firearm is clear of ammunition.
- **Use of Tools:** When using tools for installation, ensure they are in good condition and appropriate for the task. Follow the manufacturer's instructions for any tools used.
- **Loctite Application:** When applying blue Loctite to the mounting screws, avoid contact with the red dot sight to prevent damage.
- **Torque Specifications:** Adhere to the specified torque of 15 in/lbs for mounting screws to prevent overtightening, which could damage the mount or firearm.

## Instructions for Installation and Usage

### 1. Remove the Rear Sight:

- Ensure your firearm is unloaded.
- Carefully remove the existing rear sight from your revolver.

### 2. Install the EGW Sight Mount:

- Place the EGW Sight Mount into the dovetail of the revolver.
- Tighten the set screw (if applicable) to secure the mount.

### 3. Attach the Red Dot Sight:

- Place the red dot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the mount to prevent Loctite from adhering to the sight.

#### 4. Secure the Red Dot Sight:

- Apply blue Loctite to the provided mounting screws.
- Torque the mounting screws to 15 in/lbs using a 5/64" allen wrench.

#### 5. Final Checks:

- Ensure everything is securely fastened before using your firearm.
- Perform a function check to ensure the red dot sight is properly aligned and operational.

## Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the sight mount or any components become damaged beyond repair, dispose of them responsibly. Check local guidelines for proper disposal methods for metal and plastic components.

## Contact Information for Further Support

For any safety inquiries or further assistance regarding the S&W K, L, N, X Frame Revolvers Vortex Razor Sight Mount, please refer to the manufacturer's website or contact their customer support for guidance.

By following these instructions and safety guidelines, you can ensure a safe and enjoyable experience with your S&W K, L, N, X Frame Revolvers Vortex Razor Sight Mount. Always prioritize safety and responsible firearm handling.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)