

MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT - EGW MOSIN NAGANT 91/93 1-PIECE UNDRILLED PICATINNY BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

EGW's Mosin Nagant mount allows you to remove the rear leaf sight and install the base without the need to unsolder anything. It is one of the most stable bases on the market and uses the rear sight housing so there are no major modifications to your rifle like with some other brands. Installation: Remove rear leaf sight from the housing Keep the original pin as you will need this to install the base Insert the tabbed side of our steel base in to the rear of the rear sight Check for fitment on the front of the steel base The corners and front may need to be filed down to achieve the optimal fit Once the base sits completely in the rear housing insert the retaining pin from the original sight Adjust the set screw to take up any play in the rail Screw the top aluminum mount to the steel base This mount can be put on in either direction EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. EGW one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. EGW machines these in thier shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type III anodized for long lasting durability. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately).



Attributes

- Name: [EGW MOSIN NAGANT 91/93 1-PIECE UNDRILLED PICATINNY BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000744
- Mfr. No.: 80244-U
- Colour: Black
- Elevation: 0 MOA
- Material: Aluminum
- Model: 93,91
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Mosin Nagant
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 102mm
- Shipping length: 229mm
- UPC: 841370115747

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for the MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT
- About Us

Safety Instruction Guide for the MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT

Introduction

Thank you for choosing the MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT by EGW. This guide provides essential safety instructions and guidelines to ensure the safe installation and use of your scope mount. Please read this guide carefully before use.

General Safety Guidelines

- Ensure safe use of this product by following these guidelines:
 - Always use the scope mount as intended and according to the manufacturer's instructions.
 - Keep the product out of reach of children and vulnerable individuals.
 - Regularly inspect the mount for any signs of wear or damage.
 - If any defects are found, discontinue use immediately and contact the manufacturer.
 - Follow all local laws and regulations regarding the use of firearms and accessories.

Specific Safety Precautions for Use

- When using the MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT, keep the following precautions in mind:
 - Do not exceed the recommended torque specifications during installation.
 - Use blue Loctite to secure screws, as per instructions, to prevent loosening during use.
 - Ensure all components are properly fitted before use to avoid accidents.
 - Use caution when removing or installing the base to avoid injury from sharp edges.
 - Always handle firearms in a safe manner, treating every firearm as if it is loaded.

Instructions for Installation and Usage

- Follow these steps for proper installation of the scope mount:
 1. Remove the rear leaf sight from the housing.
 2. Keep the original pin, as it will be needed to install the base.
 3. Insert the tabbed side of the steel base into the rear of the rear sight.
 4. Check for fitment on the front of the steel base. The corners and front may need to be filed down for optimal fit.
 5. Once the base sits completely in the rear housing, insert the retaining pin from the original sight.
 6. Adjust the set screw to take up any play in the rail.
 7. Screw the top aluminum mount to the steel base. This mount can be installed in either direction.
 8. Measure the hole spacing in your receiver to confirm it matches the published dimensions.
 9. Ensure that Picatinny cross slots run the full length of the rail for flexibility in mounting scope rings and accessories.
- Recommended installation specifications:
 - Torque: 20 inch lbs
 - Use a drip of blue Loctite (sold separately).

Disposal Instructions

- To dispose of the MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT:
 - Follow local regulations for the disposal of metal products.

- Do not dispose of in regular household waste.
- Consider recycling options for aluminum and steel components.

Contact Information for Further Support

- For any safety inquiries or further support, please refer to the manufacturer's contact information, which can typically be found on their website or product packaging.

By following these guidelines and instructions, you can ensure the safe and effective use of your MOSIN NAGANT 91/30 HD PICATINNY SCOPE MOUNT. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk