

# AR-15/ 308 AR ADJUSTABLE TRIGGER SYSTEM - J P ENTERPRISES .154" STANDARD 3.5 LB. ADJUSTABLE TRIGGER KIT

[Rifle Parts](#) > [Triggers Parts](#) > [Triggers](#)

## Smooth, Even Trigger Pull, Precise Letoff; Easy Installation

Easy-to-fit replacement for factory trigger is fully adjustable for engagement and overtravel, and is available with pull weight as light as 3.5 lbs. Redesigned sear geometry and advanced metallurgy result in a precision-ground sear edge that delivers a precise, consistent letoff and prevents the kind of wear that causes doubling and other problems. Extremely short reset enables fast follow-up shots, a critical advantage on tactical and competition rifles.

Machined to exceptionally tight tolerances from hardened steel, and installs in minutes with no permanent alterations to the rifle. Lets you upgrade an AR-15 or an AR-style .308 rifle that uses an AR-15 trigger, while keeping your current hammer and pins. Disconnector spring, engagement screw, and overtravel screw are already installed; also includes disconnector, trigger return spring, hammer spring, and .050" hex key. Use with J.P. Enterprises Speed Hammer (available separately) for best performance. Comes with a standard weight hammer spring, for a trigger pull of between 3 and 3.5 lbs.—perfect for competition and recreational shooting—plus a “tactical” spring that gives a 3.5 to 4 lb. for applications demanding a high level of ignition reliability, including police/military use, mil-spec ammunition with hard primers, and in AR-style .308 rifles. JPFC-1 fits rifles with standard .154" diameter trigger/hammer pin holes.



## Attributes

- Name: [J P ENTERPRISES .154" STANDARD 3.5 LB. ADJUSTABLE TRIGGER KIT](#)
- Manufacturer: [J P ENTERPRISES](#)
- Product no.: 452015000
- Mfr. No.: JPFC-1
- Make: AR .308
- Style: Adjustable,Kit
- Delivery weight: 0.181kg
- UPC: 812872022079

## Item details

Made in USA

US export classification: 0A501.c

# Table of Contents

- Startpage
- AR15/308 AR Adjustable Trigger System Safety Instructions
- About Us

# AR15/308 AR Adjustable Trigger System Safety Instructions

## Introduction

Thank you for choosing the J P Enterprises AR15/308 AR Adjustable Trigger System. This product is designed to enhance the performance of your rifle while ensuring safety during use. Please read this safety instruction guide carefully to understand how to use, install, and maintain the trigger system safely.

## General Safety Guidelines

- Always treat every firearm as if it is loaded.
- Keep the firearm pointed in a safe direction at all times.
- Be aware of your surroundings and ensure that no one is in your line of fire.
- Ensure that the firearm is unloaded before performing any maintenance or installation of the trigger system.
- Store the firearm and trigger system in a secure place, out of reach of children and unauthorized users.
- Regularly inspect the trigger system for wear or damage before each use.
- Follow all local laws and regulations regarding firearm ownership and usage.

## Specific Safety Precautions for Use

- Do not use the trigger system with ammunition that is not compatible with your firearm.
- Ensure that the trigger system is installed correctly to avoid malfunction.
- Avoid using excessive force when adjusting the trigger pull weight.
- If you experience any malfunctions or irregularities while using the firearm, cease use immediately and consult a qualified gunsmith.
- Use the trigger system only with compatible AR15 or ARstyle .308 rifles.
- Always wear appropriate eye and ear protection when using firearms.

## Instructions for Installation and Usage

### Installation Instructions

#### 1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather all necessary tools, including the .050" hex key provided.

#### 2. Removing the Old Trigger:

- Follow the manufacturer's instructions for your specific rifle model to safely remove the existing trigger.
- Keep all components, such as the hammer and pins, as they will be reused.

#### 3. Installing the Trigger System:

- Carefully install the J P Enterprises trigger system into the trigger housing.
- Ensure that the disconnector spring, engagement screw, and overtravel screw are properly positioned.
- Reinstall the hammer and pins, ensuring they fit securely.

#### 4. Adjusting the Trigger:

- Use the engagement screw to adjust the trigger pull weight between 3 and 3.5 lbs for competition or recreational shooting.
- For tactical applications, use the provided tactical spring for a pull weight of 3.5 to 4 lbs.
- Test the trigger for smooth operation and proper reset before use.

#### 5. Final Checks:

- Conduct a function test to ensure the trigger operates correctly.
- If any issues are detected, consult a qualified gunsmith before using the firearm.

### Usage Instructions

- Always ensure the firearm is pointed in a safe direction when handling.
- Test the trigger system in a controlled environment before using it in the field.
- Familiarize yourself with the trigger's feel and reset to ensure safe and effective operation.

### Disposal Instructions

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- If the trigger system is damaged beyond repair, consult local regulations for proper disposal methods.
- Do not dispose of the product in regular household waste if it contains hazardous materials.

### Contact Information for Further Support

For any inquiries or support regarding the J P Enterprises AR15/308 AR Adjustable Trigger System, please refer to the manufacturer's contact details provided in the product documentation.

By following these safety instructions, you can ensure a safe and enjoyable experience with your new adjustable trigger system. Always prioritize safety and responsibility when handling firearms.

# About Us

## **Brownells Europe**

### **Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

P.O.Box 4300   
Warwick   
CV34 9BR

[www.brownells.eu](http://www.brownells.eu)