

MAUSER 91 MODEL 57 SMET - LYMAN MAUSER 91 ADJUSTABLE TANG SIGHT MODEL 57 SMET BLACK

[Rifle Parts](#) > [Sights](#) > [Rear Sights](#)

Rugged and precise sights, machined to hug the receiver for lowest line of sight, least protrusion. Audible-click, $\frac{1}{4}$ " minute adjustments for elevation and windage. Elevation slide is scribed in 3 minute increments. Quick release allows slide to be removed with a press of a button. Elevation stop screw permits instantaneous return to zero.



Attributes

- Name: [LYMAN MAUSER 91 ADJUSTABLE TANG SIGHT MODEL 57 SMET BLACK](#)
- Manufacturer: [LYMAN](#)
- Product no.: 539057007
- Mfr. No.: 3572091
- Color: Black
- Make: Mauser
- Model: 91
- Style: Adjustable,Tang Sights
- Delivery weight: 0.118kg
- UPC: 011516320919

Item details

Made in USA

Table of Contents

- Startpage
- MAUSER 91 MODEL 57 SMET LYMAN MAUSER 91 ADJUSTABLE TANG SIGHT SAFETY INSTRUCTION GUIDE
- About Us

MAUSER 91 MODEL 57 SMET LYMAN MAUSER 91 ADJUSTABLE TANG SIGHT SAFETY INSTRUCTION GUIDE

Introduction

Thank you for choosing the MAUSER 91 MODEL 57 SMET LYMAN MAUSER 91 ADJUSTABLE TANG SIGHT. This guide provides important safety information and instructions to ensure safe and effective use of the product. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Always follow the manufacturer's instructions for installation and usage.
- Check the product for any damage before use. Do not use if damaged.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about product recalls and safety updates via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Hazard Identification:**
 - Improper installation may lead to malfunction or inaccurate aiming.
 - Adjustments to the sight should be made carefully to avoid sudden changes in elevation or windage.
- **Avoiding Hazards:**
 - Use the sight only on compatible firearms as specified by the manufacturer.
 - Ensure the firearm is unloaded before installing or adjusting the sight.
 - Do not attempt to modify the sight beyond the manufacturer's specifications.
 - Always check the elevation and windage settings before use to ensure accuracy.

Instructions for Installation and Usage

• Installation:

1. Ensure the firearm is unloaded and pointed in a safe direction.
2. Locate the receiver of the firearm where the tang sight will be mounted.
3. Align the sight with the mounting holes on the receiver.
4. Secure the sight using the provided screws, ensuring they are tightened but not overtorqued.
5. Check for stability and alignment before proceeding to adjustments.

• Usage:

1. To adjust elevation, use the audibleclick mechanism to make $\frac{1}{4}$ " minute adjustments.
2. For windage adjustments, follow the same audibleclick system.
3. The elevation slide is marked in 3 minute increments for easy reference.
4. Use the quickrelease feature to remove the slide if necessary.
5. The elevation stop screw allows for an instantaneous return to zero. Make sure it is properly set before each use.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic and metal waste.
- Do not dispose of the product in regular household waste.
- Consider recycling options for metal components where available.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please refer to the manufacturer's contact information provided with the product packaging. It is important to have access to support for any concerns that may arise during the use of this product.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities.

About Us

Brownells Europe

Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

P.O.Box 4300
Warwick
CV34 9BR

www.brownells.eu