

TANG SIGHT SCREW SET - MARBLE ARMS ROSSI 1892 TANG SIGHT SCREW SET BLACK

[Rifle Parts](#) > [Sights](#) > [Sight Parts](#) > [Rear Sight Screws](#)

Tang sight screw sets for your tang sights. Find the correct screw by looking at this chart.



Attributes

- Name: [MARBLE ARMS ROSSI 1892 TANG SIGHT SCREW SET BLACK](#)
- Manufacturer: [MARBLE ARMS](#)
- Product no.: 579000101
- Mfr. No.: 995002
- Colour: Black
- Model: 1892
- Weapon type: Rossi
- Delivery weight: 0.009kg
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 871373004526

Item details

Made in USA

Table of Contents

- Startpage
- TANG SIGHT SCREW SET MARBLE ARMS ROSSI 1892 Safety Instruction Guide
- About Us

TANG SIGHT SCREW SET MARBLE ARMS ROSSI 1892 Safety Instruction Guide

Introduction

Thank you for choosing the TANG SIGHT SCREW SET by MARBLE ARMS for your Rossi 1892. This safety instruction guide provides essential information to ensure the safe and effective use of your product. Please read this guide carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the screws for wear or damage.
- Avoid using the product if any parts are missing or damaged.
- Report any unsafe products or incidents to the relevant authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always handle screws with care to avoid injury.
- Use appropriate tools when installing or adjusting screws to prevent slipping.
- Do not overtighten screws, as this may damage the sight or the firearm.
- Make sure that the firearm is unloaded before installing or making adjustments.
- Follow all relevant firearm safety regulations and guidelines during use.

Instructions for Installation and Usage

1. Preparation:

- Ensure that the firearm is unloaded and pointed in a safe direction.
- Gather all necessary tools for installation (e.g., screwdriver).

2. Installation:

- Locate the tang sight on your Rossi 1892.
- Identify the correct screw using the provided chart.
- Align the screw with the tang sight hole.
- Gently insert the screw and begin tightening it by hand.
- Use the screwdriver to securely tighten the screw, being careful not to overtighten.

3. Usage:

- After installation, verify that the sight is securely attached.
- Test the sight alignment before use to ensure accuracy.
- Regularly check the tightness of the screws during routine maintenance.

Disposal Instructions

- Dispose of any damaged or unused screws responsibly.
- Follow local regulations for the disposal of metal products.
- Do not dispose of screws in a manner that could pose a hazard to the environment.

Contact Information for Further Support

For any questions or concerns regarding the TANG SIGHT SCREW SET, please reach out to your local retailer or manufacturer support. Ensure you have the product details and any relevant information ready for assistance.

By following these guidelines, you can ensure the safe use of the TANG SIGHT SCREW SET and contribute to a safer environment for yourself and others. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk