

SEMI-AUTO SIGHT MOVER - MGW FLAT-SIDE SIGHT MOVER FOR GLOCK®

[Gunsmith Tools](#) > [Sight & Scope Installation Tools](#) > [Sight Movers](#)

Adjusts, Removes & Installs Sights Without Damage

Safely moves fixed sights right or left in their dovetails without deforming slide or sight. Specifically designed for use with factory and aftermarket Tritium night sights, which are too fragile for the traditional hammer-and-punch sight installation method; works equally well with iron sights. Thumbscrew securely locks the slide so it's fully supported in the rigid, machined aluminum body. Separate slots in the screw mechanism engage the sight and firmly, yet gently, concentrate screw force to loosen sights from even extremely tight dovetails. Hardened steel handle provides plenty of leverage, while self-lubricating, oil-impregnated Oilite® bronze bearings and extra-fine threads ensure smooth, precise movement. Beretta/Glock fit rear sights only. Glock Flat-Side fits aftermarket rear sights with straight, non-sloped sides for standard- and large-frame Glock pistols. SIG fits rear sights on all SIGs except SIG-PRO. 1911 will not work with most Kimber slide/sight combinations. Only works on rear sights. Not for installing or adjusting front sights.



Attributes

- Name: [MGW FLAT-SIDE SIGHT MOVER FOR GLOCK®](#)
- Manufacturer: [MGW](#)
- Product no.: 584000004
- Mfr. No.: MGW309S
- Model: Universal Handguns
- Weapon type: Glock
- Delivery weight: 0.748kg
- Shipping height: 56mm
- Shipping width: 117mm
- Shipping length: 224mm

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SEMIAUTO SIGHT MOVER MGW FLATSIDE SIGHT MOVER FOR GLOCK®
- About Us

Safety Instruction Guide for SEMIAUTO SIGHT MOVER MGW FLATSIDE SIGHT MOVER FOR GLOCK®

Introduction

Thank you for choosing the SEMIAUTO SIGHT MOVER MGW FLATSIDE SIGHT MOVER FOR GLOCK®. This tool is designed to safely move fixed sights on your firearm without damaging the slide or sight. Please read and follow this safety instruction guide to ensure safe usage and compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always use the sight mover in a welllit and clean environment.
- Ensure that the firearm is unloaded before using the sight mover.
- Keep the sight mover out of reach of children and unauthorized users.
- Regularly inspect the sight mover for any signs of damage or wear before each use.
- Follow all local laws and regulations regarding firearm maintenance and modifications.
- If you encounter any difficulties or uncertainties while using the product, seek assistance from a qualified professional.

Specific Safety Precautions for Use

- **Hazard Identification:**
 - Potential pinch points exist when operating the thumbscrew and when positioning the sight mover.
 - Improper handling may cause injury or damage to the firearm.
- **Avoiding Hazards:**
 - Always keep fingers and other body parts away from moving parts during operation.
 - Do not force the sight mover if it does not operate smoothly; check for obstructions or misalignment.
 - Ensure that the sight is securely locked before applying any force to adjust it.
- **Age and Audience Specific Warnings:**
 - This product is intended for use by adults only. Do not allow children to operate the sight mover.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is unloaded and placed on a stable surface.
- Identify the sight you wish to adjust.

2. Setting Up the Sight Mover:

- Position the sight mover over the sight to be adjusted.
- Use the thumbscrew to securely lock the slide of the firearm into the sight mover's body.

3. Adjusting the Sight:

- Engage the screw mechanism to apply gentle pressure to the sight.
- Turn the thumbscrew clockwise to loosen the sight from its dovetail.
- If resistance is felt, do not force the sight; instead, check for proper alignment and lubrication.

4. Finalizing Adjustments:

- Once the sight is moved to the desired position, ensure it is firmly seated in the dovetail.
- Recheck the security of the sight using the thumbscrew before removing the sight mover.

5. Completion:

- Carefully remove the sight mover from the firearm.
- Inspect the sight to ensure it is properly aligned and secure.

Disposal Instructions

- Dispose of the sight mover in accordance with local regulations.
- If the tool is damaged beyond repair, consider recycling materials where possible.
- Do not dispose of the sight mover in regular household waste.

Contact Information for Further Support

For any inquiries regarding safety or product support, please refer to the manufacturer's contact information provided with your product.

Thank you for your attention to these safety instructions. Your safety and the proper functioning of your firearm are our top priorities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk