

COMBINATION TOOL for GLOCK® - B & J MACHINE SIGHT TOOL FOR GLOCK

[Gunsmith Tools](#) > [Handgun Tools](#) > [Sight Tools](#)

Handy Tool Makes Glock Sight Changes Easier

Easy-to-use tool helps you remove factory front sights and install aftermarket sights. The punch is just the right size for depressing front sight center spreader; hex wrench holds and tightens the small retaining nut for the replacement sight. Non-slip knurled grip.



Attributes

- Name: [B & J MACHINE SIGHT TOOL FOR GLOCK](#)
- Manufacturer: [B & J MACHINE](#)
- Product no.: 694301100
- Mfr. No.:
- Model: Universal Handguns
- Weapon type: Glock
- Delivery weight: 0.023kg
- Shipping height: 3mm
- Shipping width: 122mm
- Shipping length: 175mm
- UPC: 617407958133

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for COMBINATION TOOL for GLOCK® B & J MACHINE SIGHT TOOL FOR GLOCK
- About Us

Safety Instruction Guide for COMBINATION TOOL for GLOCK® B & J MACHINE SIGHT TOOL FOR GLOCK

Introduction

Thank you for choosing the COMBINATION TOOL for GLOCK® B & J MACHINE SIGHT TOOL. This tool is designed to help you safely remove factory front sights and install aftermarket sights on your Glock handgun. Please read this safety instruction guide carefully before use to ensure your safety and the proper functioning of the tool.

General Safety Guidelines

- Always follow the manufacturer's instructions when using this tool.
- Ensure that the firearm is unloaded before using the tool.
- Store the tool in a safe place out of reach of children and unauthorized users.
- Inspect the tool for any signs of damage before each use. Do not use if damaged.
- Use the tool only for its intended purpose. Misuse may result in injury or damage.
- Report any unsafe conditions or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Use protective eyewear to shield your eyes from potential debris when using the tool.
- Ensure your hands are dry and free of any oils or substances that may affect grip.
- Use the tool in a welllit area to ensure visibility and accuracy during use.
- Do not apply excessive force when using the punch or wrench to avoid damaging the tool or the firearm.
- Keep the working area clear of distractions and clutter to maintain focus.

Instructions for Installation and Usage

1. Preparation

- Ensure that your Glock handgun is unloaded and pointed in a safe direction.
- Gather all necessary tools and materials, including the COMBINATION TOOL for GLOCK.

2. Removing Factory Front Sight

- Position the punch against the front sight center spreader.
- Carefully depress the center spreader using the punch until the front sight loosens.
- Remove the factory front sight from the slide.

3. Installing Aftermarket Sight

- Align the aftermarket sight with the mounting slot on the slide.
- Use the hex wrench to hold and tighten the small retaining nut for the replacement sight.
- Ensure the sight is securely attached and properly aligned.

4. Final Check

- Inspect the installation to ensure that the sight is secure and correctly positioned.
- Store the tool in a safe location after use.

Disposal Instructions

- Dispose of the tool in accordance with local regulations for metal and plastic waste.
- If the tool is damaged beyond repair, ensure it is disposed of in a manner that prevents accidental injury to others.

Contact Information for Further Support

For any inquiries regarding safety or usage of the COMBINATION TOOL for GLOCK®, please contact the manufacturer or refer to the official website for support.

By following these guidelines, you can ensure safe and effective use of the COMBINATION TOOL for GLOCK® B & J MACHINE SIGHT TOOL. Thank you for prioritizing safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk