

# SIG SAUER 320 TAKE DOWN LEVER O-RING

[Handgun Parts](#) > [Frame Parts](#) > [Disassembly Parts](#) > [Levers & Latches](#)

Sig Sauer factory Take Down Lever O-Ring for the P320.



## Attributes

- Name: [SIG SAUER 320 TAKE DOWN LEVER O-RING](#)
- Manufacturer: [SIG SAUER, INC.](#)
- Product no.: 732000611
- Mfr. No.: 38000144-R
- Make: Sig Sauer
- Model: P320
- Delivery weight: 0.045kg
- Shipping height: 3mm
- Shipping width: 102mm
- Shipping length: 191mm
- UPC: 798681479580

## Item details

Made in USA

US export classification: 0A501.x

# Table of Contents

- [Startpage](#)
- [SIG SAUER 320 Take Down Lever ORing Safety Instruction Guide](#)
- [About Us](#)

# SIG SAUER 320 Take Down Lever ORing Safety Instruction Guide

## Introduction

Thank you for choosing the SIG SAUER 320 Take Down Lever ORing for your P320 firearm. This guide provides essential safety instructions and information to ensure the safe use and maintenance of this product. Please read this guide carefully before installation and use.

## General Safety Guidelines

- Ensure that the firearm is unloaded before performing any maintenance or installation.
- Always handle firearms with care and follow the manufacturer's safety instructions.
- Keep this product out of reach of children and unauthorized users.
- Regularly inspect the Take Down Lever ORing for wear or damage. Replace it if necessary.
- Report any unsafe products or accidents to the appropriate authorities.

## Specific Safety Precautions for Use

- Only use the SIG SAUER 320 Take Down Lever ORing with the P320 model.
- Do not use the product if it appears damaged or worn.
- Ensure that all parts are compatible before installation.
- Follow all local laws and regulations regarding firearm modifications and maintenance.
- Wear safety glasses when working on your firearm to protect your eyes from potential debris.

## Instructions for Installation and Usage

### 1. Preparation

- Ensure that your P320 is completely unloaded and pointed in a safe direction.
- Gather necessary tools: a small screwdriver may be required for installation.

### 2. Removing the Old ORing

- Locate the existing Take Down Lever ORing.
- Carefully remove the old ORing from the lever using a small screwdriver if necessary.
- Inspect the area for any debris or residue and clean it if needed.

### 3. Installing the New ORing

- Take the new SIG SAUER 320 Take Down Lever ORing out of the packaging.
- Position the new ORing onto the Take Down Lever.
- Ensure that the ORing is seated properly and fits snugly.

### 4. Final Checks

- Reassemble the firearm according to the manufacturer's instructions.
- Perform a function check to ensure that the Take Down Lever operates smoothly.
- Store the firearm safely and securely.

## Disposal Instructions

- Dispose of the old ORing in accordance with local waste disposal regulations.

- If the product is damaged beyond repair, dispose of it in a manner that prevents it from being reused or causing harm.

## **Contact Information for Further Support**

For any questions or concerns regarding the SIG SAUER 320 Take Down Lever ORing, please contact the manufacturer or authorized dealer. Ensure that you have the product details ready for assistance.

Thank you for your attention to these safety instructions. Your safety and the safety of others depend on the proper use and maintenance of your SIG SAUER 320 Take Down Lever ORing.

# About Us

## Brownells Česká republika

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.cz](http://www.brownells.cz)