

AR-15/M16 D-FENDER EXTRACTOR D-RING - M G I D-FENDER D-RING

[Home](#)

Drop-On Installation Gives A Lifetime Of Improved Extraction

Firm, rubber, D-shaped ring surrounds the extractor spring to multiply extractor spring tension by 400%. Easy installation prevents virtually all extraction problems associated with AR-15 and M16 firearms.



Attributes

- Name: [M G I D-FENDER D-RING](#)
- Manufacturer: [M G I](#)
- Product no.: 741015003
- Mfr. No.: NONE
- Weapon type: AR-15
- Delivery weight: 0.005kg
- Shipping height: 8mm
- Shipping width: 51mm
- Shipping length: 127mm
- UPC: 094922878946

Item details

Made in USA

Table of Contents

- Startpage
- AR15/M16 DFENDER EXTRACTOR DRING Safety Instructions
- About Us

AR15/M16 DFENDER EXTRACTOR DRING Safety Instructions

Introduction

Thank you for choosing the AR15/M16 DFENDER EXTRACTOR DRING by M G I. This product is designed to enhance the performance of your firearm by improving extractor spring tension. To ensure safe and effective use, please read and follow these safety instructions carefully.

General Safety Guidelines

- Always treat firearms as if they are loaded.
- Ensure you are in a safe environment when handling or installing this product.
- Keep this product out of reach of children and unauthorized users.
- Always follow the manufacturer's guidelines for your specific firearm model.
- Regularly inspect your firearm and its components for wear or damage.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Use only with AR15 and M16 firearms as intended.
- Do not modify the DFENDER EXTRACTOR DRING in any way.
- Ensure the firearm is unloaded before installation.
- Wear appropriate safety gear, including eye protection, when handling firearms.
- Be aware of your surroundings and ensure a safe backdrop when firing.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools for installation, if required.

2. Installation:

- Locate the extractor spring on your AR15 or M16 firearm.
- Remove the existing extractor spring carefully.
- Place the DFENDER EXTRACTOR DRING around the extractor spring.
- Reinstall the extractor spring with the DRING in place.
- Ensure the DRING is securely positioned and does not interfere with the operation of the extractor.

3. Usage:

- After installation, perform a function check to ensure the extractor operates correctly.
- Regularly inspect the DRING for wear or damage during routine firearm maintenance.
- If you experience any extraction problems, consult a qualified gunsmith.

Disposal Instructions

- Dispose of the DFENDER EXTRACTOR DRING according to local regulations.
- Do not dispose of the product in regular household waste.
- Check with local authorities for proper disposal methods for rubber products.

Contact Information for Further Support

For any inquiries or support regarding the AR15/M16 DFENDER EXTRACTOR DRING, please refer to the manufacturer's contact information provided with your product.

By following these guidelines, you can help ensure the safe and effective use of the AR15/M16 DFENDER EXTRACTOR DRING. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk