

TITANIUM NITRIDE NECK BUSHINGS - REDDING TITANIUM NITRIDE BUSHING/.367

[Reloading](#) > [Reloading Dies](#) > [Neck Size Bushings](#)

Heat treated steel bushings as above, but with the addition of a Titanium Nitride coating to further increase the effective surface hardness and reduce sizing friction. Bushings are available throughout the range of .185" thru .368" in .001" increments. The last three digits of the part (#RD76XXX) denotes bushing size. .185 to .252 .253 to .305 .306 to .368



Determining Redding Bushing Size

The proper bushing size can be easily determined by measuring the outside neck diameter of your loaded cartridges with a precision micrometer or a dial caliper. Then, simply subtract .001" from the cartridge that had the smallest average neck diameter. This diameter bushing will generally size case necks just enough to create the proper press fit for the bullet.

If you are using a Type "S" style die and not turning the outside of your case necks, we suggest using a bushing .002" smaller than your smallest average neck diameter, and using the expander ball included with your Type "S" die. This size bushing will still give you minimal sizing (maximizing the life of your brass) and the expander ball will insure that each cartridge has the same bullet grip.

Redding has found that when you have cases with neck wall thicknesses on the thin side of the SAAMI tolerance, your fired case will measure considerably larger (.006" to .010" larger) than your loaded rounds. In these circumstances, Redding's tests have shown that a bushing .001" larger (than the loaded round) may give you the desired bullet grip.

Attributes

- Name: [REDDING TITANIUM NITRIDE BUSHING/.367](#)
- Manufacturer: [REDDING](#)
- Product no.: 749003390
- Mfr. No.: 76367
- Diameter (in): .367
- Delivery weight: 0.009kg
- Shipping height: 1mm
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 611760763670

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for TITANIUM NITRIDE NECK BUSHINGS
- About Us

Safety Instruction Guide for TITANIUM NITRIDE NECK BUSHINGS

Introduction

Thank you for choosing the Redding Titanium Nitride Neck Bushings. These bushings are designed to enhance your reloading experience by providing superior surface hardness and reducing sizing friction. To ensure safe and effective use, please read this safety instruction guide carefully.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the bushings by following all instructions and guidelines.
- **Enhanced Recalls:** Stay informed about any recall notices regarding this product and follow the instructions provided for safe return or remedy.
- **Online Shopping Protections:** If purchased online, ensure the platform complies with safety standards.
- **Vulnerable Groups:** Keep the product out of reach of children and ensure that it is used only by individuals familiar with reloading equipment.
- **EU Contact Point:** For safety inquiries, refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Check the EU's Safety Gate platform for updates on product safety and recalls.

Specific Safety Precautions for Use

- **Wear protective gear:** Always wear safety glasses and gloves when handling and using the bushings.
- **Inspect before use:** Check the bushings for any signs of damage or wear before installation.
- **Avoid misuse:** Do not use the bushings for purposes other than intended. They are specifically designed for reloading applications.
- **Keep work area clean:** Maintain a tidy work area to prevent accidents and ensure safe handling of materials.
- **Follow manufacturer guidelines:** Adhere strictly to the manufacturer's instructions for installation and usage.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools and materials required for installation.
- Ensure that your work area is clean and welllit.

2. Installation:

- Select the appropriate bushing size based on your reloading needs. The last three digits of the part number (#RD76XXX) denote the bushing size.
- Carefully remove the bushing from its packaging.
- Install the bushing into your resizing die according to the manufacturer's instructions. Ensure it is securely fitted.

3. Usage:

- During reloading, monitor the bushing for any signs of wear or damage.
- Use the bushing only within the specified diameter range of .185" thru .368" in .001" increments.
- If you encounter any issues or abnormalities during use, stop immediately and inspect the bushing.

Disposal Instructions

- Dispose of any damaged or worn bushings in accordance with local regulations for metal waste.
- Do not throw bushings in regular household waste. Check with local waste management for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the use of your Titanium Nitride Neck Bushings, please refer to the contact information provided by your retailer or manufacturer. They are equipped to assist you with safety inquiries or product support.

By following these safety instructions, you can ensure a safe and effective reloading experience with your Redding Titanium Nitride Neck Bushings. Thank you for prioritizing safety in your reloading practices.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk