

TITANIUM NITRIDE NECK BUSHINGS - REDDING TITANIUM NITRIDE BUSHING/.361

[Reloading](#) > [Reloading Dies](#) > [Neck Size Bushings](#)

Heat treated steel bushings as above, but with the addition of a Titanium Nitride coating to further increase the effective surface hardness and reduce sizing friction. Bushings are available throughout the range of .185" thru .368" in .001" increments. The last three digits of the part (#RD76XXX) denotes bushing size. .185 to .252 .253 to .305 .306 to .368



Determining Redding Bushing Size

The proper bushing size can be easily determined by measuring the outside neck diameter of your loaded cartridges with a precision micrometer or a dial caliper. Then, simply subtract .001" from the cartridge that had the smallest average neck diameter. This diameter bushing will generally size case necks just enough to create the proper press fit for the bullet.

If you are using a Type "S" style die and not turning the outside of your case necks, we suggest using a bushing .002" smaller than your smallest average neck diameter, and using the expander ball included with your Type "S" die. This size bushing will still give you minimal sizing (maximizing the life of your brass) and the expander ball will insure that each cartridge has the same bullet grip.

Redding has found that when you have cases with neck wall thicknesses on the thin side of the SAAMI tolerance, your fired case will measure considerably larger (.006" to .010" larger) than your loaded rounds. In these circumstances, Redding's tests have shown that a bushing .001" larger (than the loaded round) may give you the desired bullet grip.

Attributes

- Name: [REDDING TITANIUM NITRIDE BUSHING/.361](#)
- Manufacturer: [REDDING](#)
- Product no.: 749003422
- Mfr. No.: 76361
- Diameter (in): .361
- Delivery weight: 0.032kg
- Shipping height: 13mm
- Shipping width: 76mm
- Shipping length: 114mm
- UPC: 611760763618

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for TITANIUM NITRIDE NECK BUSHINGS
- About Us

Safety Instruction Guide for TITANIUM NITRIDE NECK BUSHINGS

Introduction

Thank you for choosing the Redding Titanium Nitride Neck Bushings. These bushings are designed to enhance your reloading experience by providing increased surface hardness and reduced sizing friction. This guide provides important safety information and instructions to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure the bushings are used only for their intended purpose in reloading applications.
- Always inspect the bushings for any signs of damage or wear before use.
- Keep bushings out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.
- Store bushings in a cool, dry place to prevent corrosion or damage.

Specific Safety Precautions for Use

- Always wear appropriate personal protective equipment (PPE) such as safety glasses and gloves when handling and using the bushings.
- Do not use the bushings if they are damaged or show signs of excessive wear.
- Ensure that the bushings are compatible with your reloading equipment.
- Follow the manufacturer's guidelines for specific sizing and usage.
- Avoid using excessive force during installation to prevent damage to the bushings or your equipment.
- Do not exceed the recommended diameter specifications for the bushings.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools and materials for installation.
- Ensure the reloading press is turned off and unplugged before beginning.

2. Installation:

- Select the appropriate bushing size based on your reloading requirements.
- Carefully insert the bushing into the designated area of your reloading die.
- Ensure the bushing is seated properly and securely.

3. Usage:

- Follow the reloading process as outlined in your reloading manual.
- Monitor the performance of the bushings during use. If you notice any irregularities, stop using them immediately.
- Clean the bushings regularly to maintain optimal performance and longevity.

4. PostUsage:

- After reloading, remove the bushings from the die and clean them thoroughly.
- Inspect the bushings for any signs of wear or damage before storing them.

Disposal Instructions

- Dispose of any damaged or worn bushings in accordance with local waste disposal regulations.
- Do not throw bushings in regular household waste if they are considered hazardous or contain materials that require special disposal methods.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please refer to the manufacturer's contact information provided with your product. Always ensure you have the relevant product details ready when seeking assistance.

By following these safety instructions, you can ensure a safe and effective reloading experience with your Redding Titanium Nitride Neck Bushings. Thank you for prioritizing safety and compliance with EU regulations.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk