

# 12 GA SLUG MOULD - LYMAN 12 GAUGE 525GR SABOT SLUG MOLD

[Reloading](#) > [Bullet Casting](#) > [Casting Moulds](#) > [Shotgun Moulds](#)

12 GA SLUG MOULD The Lyman Sabot slug is designed to fit standard shotgun wads and star crimped. No special roll crimping tools necessary. Uses Standard Plastic Wads.



## Attributes

- Name: [LYMAN 12 GAUGE 525GR SABOT SLUG MOLD](#)
- Manufacturer: [LYMAN](#)
- Product no.: 749012457
- Mfr. No.: 2654112
- Delivery weight: 0.386kg
- Shipping height: 51mm
- Shipping width: 53mm
- Shipping length: 109mm
- UPC: 011516241122

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for 12 GA SLUG MOULD LYMAN 12 GAUGE 525GR SABOT SLUG MOLD
- About Us

# Safety Instruction Guide for 12 GA SLUG MOULD LYMAN 12 GAUGE 525GR SABOT SLUG MOLD

## Introduction

Thank you for purchasing the 12 GA SLUG MOULD LYMAN 12 GAUGE 525GR SABOT SLUG MOLD. This guide provides essential safety instructions to ensure safe usage and maintenance of the product. Please read this document carefully before using the mould to prevent accidents and ensure a safe experience.

## General Safety Guidelines

- Always follow safety instructions provided in this guide.
- Ensure the product is used only for its intended purpose.
- Keep the mould out of reach of children and vulnerable individuals.
- Regularly inspect the mould for any signs of damage or wear before use.
- Use personal protective equipment (PPE) such as gloves and safety goggles when handling lead and using the mould.
- Store the mould in a cool, dry place away from direct sunlight and moisture.

## Specific Safety Precautions for Use

- Avoid inhaling fumes from heated lead; use in a wellventilated area.
- Do not exceed the recommended temperature when melting lead.
- Ensure that the sprue cutter is functioning correctly to prevent lead spills.
- Be cautious of sharp edges on the mould; handle with care.
- Keep the working area clean to avoid accidents from lead spills or other hazards.

## Instructions for Installation and Usage

### 1. Setup:

- Ensure the work area is clean, dry, and wellventilated.
- Gather all necessary tools and materials, including a lead melting pot and personal protective equipment.

### 2. Melting Lead:

- Use a lead melting pot to melt the lead to the recommended temperature.
- Monitor the lead closely to avoid overheating.

### 3. Using the Mould:

- Pour the molten lead into the mould cavities carefully.
- Allow the lead to cool and solidify according to the manufacturer's guidelines.
- Use the builtin sprue cutter to trim excess lead once cooled.

### 4. PostUse Care:

- Clean the mould after each use to prevent corrosion and maintain performance.
- Store the mould in a safe location, ensuring it is dry and free from contaminants.

## **Disposal Instructions**

- Dispose of any lead waste and excess material in accordance with local regulations.
- Do not dispose of lead in regular household waste; check with local authorities for proper disposal methods.

## **Contact Information for Further Support**

For any safety inquiries or support regarding this product, please contact the manufacturer or refer to the product's official website for further assistance.

By following these guidelines, you can ensure a safe and efficient experience while using the 12 GA SLUG MOULD LYMAN 12 GAUGE 525GR SABOT SLUG MOLD. Always prioritize safety and report any unsafe conditions to the appropriate authorities. Thank you for your attention to these important safety instructions.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)