

LUBE-A-MATIC-2 TOP PUNCHES - RCBS #638 TOP PUNCH

[Reloading](#) > [Bullet Casting](#) > [Top Punches](#)

RCBS Top Punches are machined to fit the bullet nose shape and prevent bullet deformation during the sizing/lubrication process. Fits RCBS Lube-A-Matic Bullet Sizer/Lubricator or Lyman 450/4500 Lube Sizer. Find the proper punch in this chart.



Attributes

- Name: [RCBS #638 TOP PUNCH](#)
- Manufacturer: [RCBS](#)
- Product no.: 749014342
- Mfr. No.: 85638
- Delivery weight: 0.068kg
- Shipping height: 10mm
- Shipping width: 51mm
- Shipping length: 152mm
- UPC: 076683856388

Item details

Made in USA

Table of Contents

- Startpage
- LUBEAMATIC2 TOP PUNCHES RCBS #638 TOP PUNCH Safety Instructions
- About Us

LUBEAMATIC2 TOP PUNCHES RCBS #638 TOP PUNCH Safety Instructions

Introduction

Thank you for choosing the LUBEAMATIC2 TOP PUNCHES RCBS #638 TOP PUNCH. This product is designed to ensure safe and effective bullet sizing and lubrication. Please read this safety instruction guide carefully to ensure proper usage and to minimize risks.

General Safety Guidelines

- Always use the product in accordance with the manufacturer's instructions.
- Ensure the work area is clean, dry, and welllit.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the product for any signs of damage or wear before use.
- Use personal protective equipment (PPE) such as safety glasses and gloves when handling the product.

Specific Safety Precautions for Use

- Do not exceed the recommended pressure or force when using the LUBEAMATIC2 TOP PUNCH.
- Avoid using the product with incompatible materials that could cause damage.
- Do not attempt to modify or alter the product in any way.
- Ensure that the product is securely attached to the LubeAMatic Bullet Sizer/Lubricator or Lyman 450/4500 Lube Sizer before use.
- In case of any malfunction or unusual operation, stop using the product immediately and consult a professional.

Instructions for Installation and Usage

1. Installation:

- Ensure the LubeAMatic Bullet Sizer/Lubricator or Lyman 450/4500 Lube Sizer is unplugged and cooled down before installation.
- Locate the appropriate size punch for your bullet nose shape using the provided chart.
- Insert the top punch into the sizing die, ensuring it is seated securely.
- Tighten the retaining screw to hold the punch in place.

2. Usage:

- Prepare the bullet by ensuring it is clean and free of debris.
- Adjust the lubricant feed to ensure proper lubrication during the sizing process.
- Insert the bullet into the sizing die and pull the handle of the LubeAMatic slowly and steadily.
- Monitor the process to ensure that the bullet is being sized correctly without deformation.
- Once completed, remove the sized bullet and inspect it for quality.

Disposal Instructions

- Dispose of any damaged or unusable products in accordance with local regulations.
- Do not dispose of the product in regular household waste. Instead, check for local recycling or hazardous waste disposal options.

Contact Information for Further Support

For any inquiries or concerns regarding the safety and use of the LUBEAMATIC2 TOP PUNCHES RCBS #638 TOP PUNCH, please reach out to your local distributor or refer to the manufacturer's website for more information.

Conclusion

Your safety is our priority. By following these guidelines and instructions, you can ensure the safe and effective use of the LUBEAMATIC2 TOP PUNCHES RCBS #638 TOP PUNCH. Always stay informed about product safety and recall updates through the EU's Safety Gate platform. Thank you for choosing our product!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk