

1/4" DRIVE TORQUE HANDLE - SEEKONK PRECISION TOOLS 45 IN/LB TORQUE HANDLE

[Gunsmith Tools](#) > [General Gunsmith Tools](#) > [Wrenches](#) > [General Wrenches](#)

Takes The Guesswork Out Of Tightening Triggerguard Screws

Improve accuracy and shot-to-shot consistency by torquing rifle triggerguard, plus any ring and base screws to the same reading every time. Convenient T handles break away at pre-set, inch/pound torque values and the back-off feature allows the screw to be removed again. Accepts all 1/4" drive attachments.



Attributes

- Name: [SEEKONK PRECISION TOOLS 45 IN/LB TORQUE HANDLE](#)
- Manufacturer: [SEEKONK PRECISION TOOLS](#)
- Product no.: 792212045
- Mfr. No.: BT2L
- Style: Torque Wrenches
- Delivery weight: 0.272kg
- Shipping height: 18mm
- Shipping width: 94mm
- Shipping length: 112mm

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for 1/4" Drive Torque Handle
- About Us

Safety Instruction Guide for 1/4" Drive Torque Handle

Introduction

Thank you for choosing the 1/4" Drive Torque Handle from Seekonk Precision Tools. This tool is designed to improve the accuracy and consistency of your torque applications, specifically for rifle trigger guards and other screws. It is essential to follow the safety instructions provided in this guide to ensure safe and effective use.

General Safety Guidelines

- Always read and understand the instructions before using the torque handle.
- Ensure that the torque handle is used only for its intended purpose.
- Keep the torque handle out of reach of children and vulnerable individuals.
- Regularly inspect the torque handle for any signs of damage or wear before use.
- Store the torque handle in a dry, safe place when not in use.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the torque handle is set to the correct torque value before use.
- Do not exceed the maximum torque value specified for your application.
- Use appropriate personal protective equipment (PPE) such as safety glasses when using the torque handle.
- Avoid using the torque handle in wet or damp conditions to prevent slippage.
- Do not use the torque handle if it is damaged or malfunctioning.
- Follow the manufacturer's recommendations for torque settings based on the application.

Instructions for Installation and Usage

1. Setting Up the Torque Handle

- Attach the desired 1/4" drive attachment to the torque handle.
- Adjust the torque setting to the required inch/pound value using the adjustment mechanism.
- Ensure the setting is locked in place to prevent accidental changes.

2. Using the Torque Handle

- Position the torque handle over the screw or fastener you intend to tighten.
- Apply steady pressure while turning the handle until you reach the preset torque value.
- Once the torque value is reached, the handle will break away, indicating that the desired torque has been achieved.
- If necessary, use the backoff feature to remove the screw or fastener.

3. PostUse Care

- After use, clean the torque handle with a dry cloth to remove any debris or residue.
- Store the torque handle in its designated case or a safe location to prevent damage.

Disposal Instructions

- Dispose of the torque handle in accordance with local regulations.
- If the product is damaged beyond repair, consider recycling materials where possible.

- Do not dispose of the torque handle in household waste.

Contact Information for Further Support

For any questions, concerns, or safety inquiries regarding the 1/4" Drive Torque Handle, please reach out to the designated contact point provided by the manufacturer.

By following these safety instructions, you can ensure the safe and effective use of the 1/4" Drive Torque Handle. Thank you for your attention to these guidelines, and happy tool handling!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk