

#3 MUZZLE BRAKE 22 CALIBER - SHREWD #3 MUZZLE BRAKE 22 CALIBER 5/8-24 CHROME MOLY SILVER

[Rifle Parts](#) > [Muzzle Devices](#) > [Compensators & Muzzle Brakes](#)

Multi-port brake softens felt recoil and reduces muzzle rise. A single expansion chamber and 42 total ports, 21 on each side, angled 7° forward, provide maximum recoil control. Gunsmithing required. Comes with a .220" (nominal) diameter exit hole that must be opened up to .020" larger than bullet diameter. Can be enlarged to allow bullets up to .44 caliber. Rear exterior of comp can be machined to conform to barrel.



Attributes

- Name: [SHREWD #3 MUZZLE BRAKE 22 CALIBER 5/8-24 CHROME MOLY SILVER](#)
- Manufacturer: [SHREWD](#)
- Product no.: 860100325
- Mfr. No.: NONE
- Finish: Silver
- Material: Chrome Moly
- Size: .850
- Threads: 5/8-24
- Weapon type: Universal Rifles
- Delivery weight: 0.113kg
- Shipping height: 18mm
- Shipping width: 124mm
- Shipping length: 226mm

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for #3 Muzzle Brake 22 Caliber
- About Us

Safety Instruction Guide for #3 Muzzle Brake 22 Caliber

Introduction

Thank you for choosing the #3 Muzzle Brake 22 Caliber by SHREWD. This product is designed to enhance shooting performance by reducing felt recoil and muzzle rise. To ensure safe and effective use of this product, please read and follow the safety guidelines and instructions provided in this manual.

General Safety Guidelines

- Always handle firearms and accessories with care and respect.
- Ensure that the muzzle brake is installed correctly to avoid accidents.
- Use only compatible firearms and ammunition with this muzzle brake.
- Regularly inspect the muzzle brake for signs of wear or damage.
- Keep this product out of reach of children and unauthorized users.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before installing or removing the muzzle brake.
- Use protective eyewear when shooting to protect against debris and noise.
- Do not exceed the maximum caliber rating of .44 when enlarging the exit hole.
- Be aware of your surroundings and ensure a safe shooting environment.
- Follow all local laws and regulations regarding the use of muzzle brakes.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded.
- Remove the existing muzzle device if applicable.
- Clean the threads of the barrel to remove any debris.
- Thread the muzzle brake onto the barrel using the 5/8x24 threads.
- Handtighten the muzzle brake, ensuring it is secure but do not overtighten.
- If necessary, use a gunsmith to machine the rear exterior to conform to the barrel.

2. Usage:

- Once installed, check the alignment of the muzzle brake.
- Fire the firearm in a safe environment, monitoring for any unusual behavior.
- If you experience excessive recoil or movement, consult a gunsmith for adjustments.

Disposal Instructions

- Dispose of this product in accordance with local regulations.
- Do not dispose of the muzzle brake in regular household waste.
- Consider recycling materials if possible.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of the #3 Muzzle Brake 22 Caliber, please reach out

to your local retailer or manufacturer. Ensure you have the product details and any relevant information ready for a more efficient response.

By following these guidelines and instructions, you can ensure the safe and effective use of the #3 Muzzle Brake 22 Caliber. Thank you for prioritizing safety while enjoying your shooting experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk