

SIGHT, FRONT BEAD (3MM OD)

[Shotgun Parts](#) > [Sights](#) > [Front Sights](#)

FITS: S686, 12, 20

FITS: All Beretta shotguns except old blade-style, and others with 2.5x.45 thread pitch



Attributes

- Name: [SIGHT, FRONT BEAD \(3MM OD\)](#)
- Manufacturer: [BERETTA USA](#)
- Product no.: 913300769
- Mfr. No.: C53675
- Make: Beretta
- Model: S686
- Sight Color: Silver
- Style: Bead
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

Table of Contents

- Startpage
- Safety Instruction Guide for SIGHT, FRONT BEAD (3MM OD)
- About Us

Safety Instruction Guide for SIGHT, FRONT BEAD (3MM OD)

Introduction

Thank you for choosing the SIGHT, FRONT BEAD (3MM OD) manufactured by Beretta USA. This safety instruction guide provides essential information to ensure safe usage and compliance with the EU General Product Safety Regulation (GPSR). Please read this guide carefully before using the product.

General Safety Guidelines

- Ensure that the product is suitable for your specific shotgun model. The SIGHT, FRONT BEAD (3MM OD) is compatible with all Beretta shotguns except old bladestyle models and those with a 2.5x.45 thread pitch.
- Always handle the product with care to avoid accidental damage or injury.
- Regularly inspect the sight for any signs of wear or damage. If any issues are found, discontinue use immediately.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Do not attempt to modify or alter the sight in any way, as this may compromise safety and functionality.
- Ensure that the shotgun is unloaded before attaching or adjusting the front bead sight.
- Always wear appropriate eye protection when handling firearms to protect against potential hazards.
- Be aware of your surroundings and ensure that you are in a safe environment when using the shotgun with the installed sight.

Instructions for Installation and Usage

1. Installation:

- Ensure that the shotgun is completely unloaded.
- Locate the front sight mounting area on your Beretta shotgun.
- Align the SIGHT, FRONT BEAD (3MM OD) with the mounting screw hole.
- Securely attach the sight using the appropriate tools, ensuring it is firmly in place.
- Doublecheck the alignment and tightness of the sight before using the shotgun.

2. Usage:

- Familiarize yourself with the sight's functionality and how it integrates with your shotgun.
- Practice aiming and shooting in a controlled environment to ensure comfort and accuracy.
- Regularly check the sight's position and integrity during use, especially after firing a significant number of rounds.

Disposal Instructions

- Dispose of the product responsibly. If the sight is damaged or no longer needed, please follow local regulations for the disposal of firearm accessories.
- Do not dispose of the sight in regular household waste. Instead, seek out local hazardous waste disposal facilities or programs.

Contact Information for Further Support

For additional support, inquiries about safety issues, or to report unsafe products, please refer to the appropriate EU contact points or safety authorities in your region. They can provide further assistance and guidance.

Thank you for your attention to these safety guidelines. Your safety and the safety of others is our top priority. Enjoy using your SIGHT, FRONT BEAD (3MM OD) safely and responsibly.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at