

T3 BATTUE FRONT SIGHT

[Rifle Parts](#) > [Sights](#) > [Front Sights](#)

FITS: Tikka T3 Battue rifles Includes: Front sight ramp, front sight (RED fiber optic), sight hood, and two sight ramp screws

NO IMAGE
AVAILABLE

Attributes

- Name: [TIKKA T3 BATTUE FRONT SIGHT](#)
- Manufacturer: [TIKKA](#)
- Product no.: 913501363
- Mfr. No.: S585T321
- Model: T3
- Style: Factory Replacement
- Weapon type: Tikka
- Delivery weight: 0.091kg
- Shipping height: 13mm
- Shipping width: 152mm
- Shipping length: 229mm

Table of Contents

- Startpage
- TIKKA T3 Battue Front Sight Safety Instruction Guide
- About Us

TIKKA T3 Battue Front Sight Safety Instruction Guide

Introduction

Thank you for choosing the TIKKA T3 Battue Front Sight. This guide provides essential safety instructions and usage information to ensure the safe operation of your front sight. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that all components are intact and free from damage before use.
- Follow all local laws and regulations regarding the use of firearms and accessories.
- Always treat firearms and their accessories with respect and caution.
- Store the product in a safe and secure location when not in use.
- Be aware of your surroundings and ensure that you are in a safe environment when using this product.

Specific Safety Precautions for Use

- Always wear appropriate eye protection when using firearms.
- Keep the front sight clean and free from obstructions that may impair visibility.
- Do not modify or alter the front sight in any way, as this may compromise safety.
- Ensure that the front sight is properly installed and secured before use.
- Regularly check the sight for wear or damage, replacing it if necessary.
- Use the front sight only with Tikka T3 Battue rifles as intended.

Instructions for Installation and Usage

1. Installation of the Front Sight:

- Gather all components: front sight ramp, front sight (RED fiber optic), sight hood, and two sight ramp screws.
- Ensure the firearm is unloaded and pointed in a safe direction.
- Remove the existing front sight if applicable.
- Align the front sight ramp with the mounting area on the rifle.
- Secure the front sight ramp in place using the two sight ramp screws provided. Ensure they are tightened but do not overtighten.
- Attach the front sight (RED fiber optic) to the front sight ramp.
- Place the sight hood over the front sight to protect it from damage.

2. Usage of the Front Sight:

- Ensure the firearm is in good working condition before use.
- Familiarize yourself with the sight picture and practice aiming in a safe environment.
- Adjust your shooting stance and grip as necessary to utilize the front sight effectively.
- Regularly check the alignment and condition of the sight during use.

Disposal Instructions

- Dispose of the front sight and its components in accordance with local regulations.
- Do not dispose of any product components in regular household waste.
- Contact your local waste management facility for proper disposal methods.

Contact Information for Further Support

For any safety inquiries or further assistance, please refer to the EU contact point for your product. Ensure that you have the product details on hand when seeking support.

By adhering to these guidelines, you can ensure safe and effective use of the TIKKA T3 Battue Front Sight. Always prioritize safety and responsible usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk