

SANDING BELTS - VSM ABRASIVES CORPORATION 1" (2.5CM) X 30" (76CM) SANDING BELT, 400 GRIT

[Gunsmith Tools](#) > [Metal Prep & Coloring](#) > [Abrasives](#) > [Sanding Belts](#)

To Fit Raytech Expanding Sanding Drums

About "Compact Grain" Belts - Aluminum Oxide Belts in super-fine grit (like 600) are only available in what the maker calls "Compact Grain". This process layers grit in a special adhesive and greatly increases belt life. Compact grain belts are easily identified; they are ugly! The 600 grit belt shown looks like it should be a 60 grit but IT ISN'T. It really will give a 600 grit finish and will last extremely well. Resin bonded, aluminum oxide. Sold singly.



Attributes

- Name: [VSM ABRASIVES CORPORATION 1" \(2.5CM\) X 30" \(76CM\) SANDING BELT, 400 GRIT](#)
- Manufacturer: [VSM ABRASIVES CORPORATION](#)
- Product no.: 925130400
- Mfr. No.:
- Grit: 400
- Size: 1 x 30
- Delivery weight: 0.095kg
- Shipping height: 28mm
- Shipping width: 102mm
- Shipping length: 325mm

Table of Contents

- Startpage
- Safety Instruction Guide for VSM Abrasives Corporation 1" (2.5CM) X 30" (76CM) Sanding Belt, 400 Grit
- About Us

Safety Instruction Guide for VSM Abrasives Corporation 1" (2.5CM) X 30" (76CM) Sanding Belt, 400 Grit

Introduction

Thank you for choosing the VSM Abrasives Corporation Sanding Belt. This guide provides important safety instructions to ensure the safe use of this product. Please read the following guidelines carefully to avoid potential hazards and to maximize the performance of your sanding belt.

General Safety Guidelines

- Ensure that the sanding belt is used only for its intended purpose.
- Always wear appropriate personal protective equipment (PPE), including safety goggles, gloves, and a dust mask, to protect against dust and debris.
- Keep the work area clean and welllit to minimize risks of accidents.
- Ensure that all tools and equipment are in good working condition before use.
- Do not use the sanding belt if it is damaged or worn.

Specific Safety Precautions for Use

- Handle the sanding belt with care to avoid cuts and abrasions.
- Do not exceed the recommended speed for the sanding belt.
- Avoid contact with the rotating sanding belt while in operation.
- Ensure that the workpiece is securely clamped or held in place to prevent movement during sanding.
- Be aware of your surroundings and keep bystanders at a safe distance while using the sanding belt.

Instructions for Installation and Usage

1. Installation:

- Ensure that the sanding machine is turned off and unplugged before installation.
- Remove any old or damaged sanding belt from the machine.
- Align the new sanding belt with the rollers and ensure it is fitted correctly.
- Tension the sanding belt according to the manufacturer's specifications.
- Plug in the machine and perform a test run to ensure proper installation.

2. Usage:

- Start the machine and allow it to reach the desired speed before beginning to sand.
- Apply light, even pressure to the workpiece. Do not force the sanding belt.
- Move the workpiece steadily across the sanding belt to achieve a uniform finish.
- Periodically check the sanding belt for wear and replace it as necessary.
- Once finished, turn off the machine and unplug it before cleaning or adjusting.

Disposal Instructions

- Dispose of the sanding belt in accordance with local waste disposal regulations.
- Do not burn the sanding belt, as it may release harmful substances.
- Consider recycling options if available in your area.

Contact Information for Further Support

For any safety inquiries or concerns regarding the VSM Abrasives Corporation Sanding Belt, please contact your local distributor or visit the manufacturer's website for more information.

Thank you for following these safety instructions. Your safety is our priority!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk