

SANDING BELTS - VSM ABRASIVES CORPORATION 1" (2.5CM) X 42" (106.7CM) SANDING BELT, 36 GRIT

[Gunsmith Tools](#) > [Metal Prep & Coloring](#) > [Abrasives](#) > [Sanding Belts](#)

To Fit Raytech Expanding Sanding Drums

About "Compact Grain" Belts - Aluminum Oxide Belts in super-fine grit (like 600) are only available in what the maker calls "Compact Grain". This process layers grit in a special adhesive and greatly increases belt life. Compact grain belts are easily identified; they are ugly! The 600 grit belt shown looks like it should be a 60 grit but IT ISN'T. It really will give a 600 grit finish and will last extremely well. Resin bonded, aluminum oxide. Sold singly.



Attributes

- Name: [VSM ABRASIVES CORPORATION 1" \(2.5CM\) X 42" \(106.7CM\) SANDING BELT, 36 GRIT](#)
- Manufacturer: [VSM ABRASIVES CORPORATION](#)
- Product no.: 925142036
- Mfr. No.:
- Grit: 36
- Size: 1 x 42
- Delivery weight: 0.05kg
- Shipping height: 28mm
- Shipping width: 53mm
- Shipping length: 460mm

Table of Contents

- Startpage
- Safety Instruction Guide for VSM Abrasives Corporation Sanding Belt
- About Us

Safety Instruction Guide for VSM Abrasives Corporation Sanding Belt

Introduction

Thank you for choosing the VSM Abrasives Corporation 1" (2.5CM) x 42" (106.7CM) Sanding Belt, 36 Grit. This guide provides important safety instructions to ensure safe and effective use of the product. Please read this guide carefully before using the sanding belt.

General Safety Guidelines

- Always ensure that the sanding belt is compatible with your sanding machine.
- Inspect the sanding belt for damage before each use. Do not use if damaged.
- Keep the work area clean and welllit to avoid accidents.
- Wear appropriate personal protective equipment (PPE) including safety goggles, dust mask, and hearing protection.
- Ensure that children and vulnerable individuals are kept away from the work area during use.

Specific Safety Precautions for Use

- Do not exceed the maximum operating speed of the sanding belt as indicated by the manufacturer.
- Do not use the sanding belt for any purpose other than its intended use.
- Avoid contact with the sanding belt while it is in motion to prevent injuries.
- Do not remove safety guards or disable safety features on your sanding machine.
- Make sure the sanding belt is properly tensioned and aligned before use.

Instructions for Installation and Usage

1. Installation:

- Turn off and unplug the sanding machine before installation.
- Remove any existing sanding belt from the machine.
- Place the new sanding belt onto the machine, ensuring that it is aligned correctly.
- Adjust the tension according to the manufacturer's instructions.
- Check that the sanding belt is securely attached before plugging in the machine.

2. Usage:

- Start the sanding machine and allow it to reach full speed before making contact with the workpiece.
- Apply light pressure while sanding to avoid damaging the material or the belt.
- Move the workpiece steadily against the sanding belt to achieve an even finish.
- Stop the machine and allow the sanding belt to come to a complete stop before making any adjustments or removing the workpiece.

Disposal Instructions

- Dispose of used sanding belts in accordance with local regulations.
- Do not dispose of sanding belts in regular household waste.
- Consider recycling options if available in your area.

Conclusion

By following these safety instructions, you can ensure safe and effective use of the VSM Abrasives Corporation Sanding Belt. If you have any concerns or questions, please consult the product packaging or contact the manufacturer directly. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk