

RUGER® MARK II™ HAMMER BUSHING - MARK II HAMMER BUSHING

[Handgun Parts](#) > [Trigger Group Parts](#) > [Hammer Parts](#) > [Hammer Bushings](#)

Close Tolerances For A Smooth, Consistent Trigger Pull

CNC machined from hardened steel to exceptionally close tolerances to help ensure a smooth, consistent trigger pull. Advanced screw machine technology is used to drill and ream the pivot pin hole perfectly concentric for optimal hammer-to-sear engagement. Black oxide finish for added durability and resistance against corrosion.



Attributes

- Name: [MARK II HAMMER BUSHING](#)
- Manufacturer: [VOLQUARTSEN](#)
- Product no.: 930000056
- Mfr. No.: VC2HB
- Make: Ruger
- Model: Mark I,Mark II
- Delivery weight: 0.005kg
- Shipping height: 8mm
- Shipping width: 71mm
- Shipping length: 86mm
- UPC: 810162012403

Item details

Made in USA

Table of Contents

- Startpage
- RUGER® MARK II™ HAMMER BUSHING SAFETY INSTRUCTIONS
- About Us

RUGER® MARK II™ HAMMER BUSHING SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the RUGER® MARK II™ Hammer Bushing. This product is designed to enhance the performance of your Ruger Mark II pistols. It is essential to read and understand the safety instructions provided in this guide to ensure safe usage and compliance with EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always handle firearms with care and respect.
- Ensure that the firearm is unloaded before performing any maintenance or installation.
- Keep the product out of reach of children and unauthorized users.
- Use only for the intended purpose as specified in the product documentation.
- Regularly check for any signs of wear or damage to the Hammer Bushing.
- Report any unsafe conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- **Personal Protective Equipment (PPE):** Always wear appropriate PPE such as safety glasses and gloves when handling the Hammer Bushing.
- **Installation Environment:** Work in a clean, dry, and welllit area to avoid accidents.
- **Avoid Force:** Do not use excessive force when installing or removing the Hammer Bushing to prevent damage to the product or firearm.
- **Compatibility Check:** Ensure that the Hammer Bushing is compatible with your specific Ruger Mark II model before installation.

Instructions for Installation and Usage

1. Preparation:

- Ensure that the firearm is completely unloaded.
- Gather necessary tools for installation, such as a screwdriver and punch.

2. Installation:

- Remove the old Hammer Bushing if applicable.
- Align the new Hammer Bushing with the pivot pin hole.
- Gently press or tap the Hammer Bushing into place using a punch, ensuring it is seated properly.
- Check for proper alignment and function before reassembling the firearm.

3. Usage:

- After installation, test the trigger pull to ensure smooth operation.
- Regularly inspect the Hammer Bushing during routine maintenance.

Disposal Instructions

- Dispose of any old or damaged Hammer Bushings in accordance with local regulations.
- Do not dispose of the product in regular household waste. Contact local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the RUGER® MARK II™ Hammer Bushing, please refer to the manufacturer's contact resources. Ensure that you have the product information available for reference.

By following these safety instructions, you can ensure a safe and effective experience with your RUGER® MARK II™ Hammer Bushing. Always prioritize safety and compliance with regulations to protect yourself and others.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at