

RUGER® MARK I/II™/III™ DRILL & TAP SCOPEMOUNT - RUGER MK I, MK II, MK III, 22/45 SCOPE MOUNT, SILVER

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Extra Low Profile Fits Drilled & Tapper Receivers

Designed to fit factory drilled and tapped receivers for fast, easy, no-gunsmithing installation. Fully contoured to fit flush on top of the receiver or barrel without unsightly gaps. Extra-strong, lightweight aluminum; accepts Weaver-style rings. Can be easily installed on non-factory drilled and tapped pistols.



Attributes

- Name: [RUGER MK I, MK II, MK III, 22/45 SCOPE MOUNT, SILVER](#)
- Manufacturer: [WEIGAND COMBAT](#)
- Product no.: 957108002
- Mfr. No.: RM2FD
- Color: Silver
- Make: Ruger
- Material: Aluminum
- Model: Mark II
- Number of Bases: 1-Piece
- Style: Weaver-Style Bases
- Delivery weight: 0.045kg
- Shipping height: 18mm
- Shipping width: 86mm
- Shipping length: 175mm

Item details

Made in USA

Table of Contents

- Startpage
- RUGER MARK I/II/III DRILL & TAP SCOPEMOUNT USER SAFETY INSTRUCTIONS
- About Us

RUGER MARK I/II/III DRILL & TAP SCOPEMOUNT USER SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the RUGER MARK I/II/III DRILL & TAP SCOPEMOUNT. This guide provides essential safety instructions to ensure safe and effective use of the product. Please read this manual carefully before installation and usage.

General Safety Guidelines

- Always ensure that the firearm is unloaded before installing or adjusting the scope mount.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the scope mount for any signs of damage or wear.
- Do not use the scope mount if it appears to be damaged or compromised.
- Follow all local laws and regulations regarding firearm modifications and accessories.
- Be aware of your surroundings and ensure a safe environment when using firearms.

Specific Safety Precautions for Use

- Ensure that the firearm is compatible with the RUGER MARK I/II/III DRILL & TAP SCOPEMOUNT.
- Use only Weaverstyle rings with this scope mount for optimal performance.
- Avoid using excessive force during installation to prevent damaging the mount or the firearm.
- Do not modify the scope mount in any way, as this may compromise safety and functionality.
- Always wear appropriate eye protection when using firearms.

Instructions for Installation and Usage

1. **Check Compatibility:** Confirm that your firearm is a RUGER Mark I, II, III, or 22/45 model.
2. **Gather Tools:** You will need a screwdriver and the included mounting screws.
3. **Prepare the Firearm:** Ensure the firearm is unloaded and pointed in a safe direction.
4. **Position the Mount:**
 - Align the scope mount with the predrilled and tapped holes on the receiver or barrel.
 - Ensure that the mount fits flush without gaps.
5. **Secure the Mount:**
 - Insert the mounting screws into the appropriate holes.
 - Tighten the screws evenly to secure the mount in place, but avoid overtightening.
6. **Attach Scope Rings:** Follow the manufacturer's instructions for installing Weaverstyle rings onto the mount.
7. **Final Check:** Inspect the installation to ensure everything is secure and properly aligned.
8. **Test the Setup:** Before using the firearm, ensure that the scope is properly zeroed and functioning as intended.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling the aluminum material if applicable.

Contact Information for Further Support

For any inquiries regarding safety or product performance, please consult your local retailer or the manufacturer's website for assistance.

Conclusion

By following these safety instructions, you can ensure the safe and effective use of the RUGER MARK I/II/III DRILL & TAP SCOPEMOUNT. Always prioritize safety and compliance with local laws while enjoying your shooting experience.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at