

XLA 6-9" Bipod - Fixed Model, Black - XLA 9-13" Bipod - Pivot Model, Black

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

The Caldwell® XLA Bipod® provides a stable shooting support that conveniently attaches to almost any firearm with a sling swivel stud. The legs are notched for easy indexing to a specific height. The bipods are available in 4 heights, black or camo and in both standard and pivoting models.

NO IMAGE
AVAILABLE

Attributes

- Name: [XLA 9-13" Bipod - Pivot Model, Black](#)
- Manufacturer: [Caldwell](#)
- Product no.: EU1001892
- Mfr. No.: 571429
- Colour: Black
- Style: Bipod
- Delivery weight: 0.5kg
- Shipping height: 149mm
- Shipping width: 64mm
- Shipping length: 267mm
- UPC: 661120714293

Table of Contents

- Startpage
- Caldwell XLA Bipod Safety Instruction Guide
- About Us

Caldwell XLA Bipod Safety Instruction Guide

Introduction

Thank you for choosing the Caldwell® XLA Bipod®. This product is designed to provide stable shooting support for various firearms. To ensure your safety and the longevity of this product, please read and follow the safety instructions outlined in this guide.

General Safety Guidelines

- Always ensure the bipod is securely attached to your firearm before use.
- Inspect the bipod for any damage or wear before each use.
- Keep the bipod clean and free from debris to maintain its functionality.
- Store the bipod in a safe, dry place when not in use.
- Be aware of your surroundings and ensure a clear shooting area.

Specific Safety Precautions for Use

- Ensure that the bipod is used only with compatible firearms that have a sling swivel stud.
- Do not exceed the weight limit of the bipod as specified in the product specifications.
- Always use the bipod on stable, flat surfaces to prevent tipping.
- Do not use the bipod in adverse weather conditions that may affect stability.
- Keep fingers and other body parts away from the bipod's moving parts during adjustment.

Instructions for Installation and Usage

Installation

1. Ensure your firearm is unloaded and pointed in a safe direction.
2. Locate the sling swivel stud on your firearm.
3. Align the bipod attachment with the sling swivel stud.
4. Securely attach the bipod to the sling swivel stud by turning the locking mechanism until it is tight.
5. Check that the bipod is firmly attached before proceeding.

Usage

1. Adjust the bipod legs to the desired height by pressing the notched indexing mechanism.
2. Ensure that both legs are set to the same height for stability.
3. Position the bipod on a stable surface.
4. Rest the firearm on the bipod and ensure it is securely supported.
5. Take your shot while maintaining control of the firearm.

Disposal Instructions

- Dispose of the bipod in accordance with local regulations.
- Do not dispose of the bipod in regular household waste.
- Consider recycling the bipod if possible, following local recycling guidelines.

Contact Information for Further Support

For any inquiries regarding safety or product information, please refer to the manufacturer's website or contact their customer support.

By adhering to these safety instructions, you can ensure a safe and enjoyable experience with your Caldwell®

XLA Bipod®. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk