

XLA 6-9" Bipod - Fixed Model, Black - XLA 13 1/2 - 27" Bipod - Pivot Model, Black

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

The Caldwell® XLA Bipod® provides a stable shooting support that conveniently attaches to almost any firearm with a sling swivel stud. The legs are notched for easy indexing to a specific height. The bipods are available in 4 heights, black or camo and in both standard and pivoting models.

NO IMAGE
AVAILABLE

Attributes

- Name: [XLA 13 1/2 - 27" Bipod - Pivot Model, Black](#)
- Manufacturer: [Caldwell](#)
- Product no.: EU1001894
- Mfr. No.: 635705
- Colour: Black
- Style: Bipod
- Delivery weight: 0.68kg
- Shipping height: 146mm
- Shipping width: 60mm
- Shipping length: 424mm
- UPC: 661120357056

Table of Contents

- Startpage
- Caldwell XLA Bipod Safety Instructions
- About Us

Caldwell XLA Bipod Safety Instructions

Introduction

Thank you for choosing the Caldwell XLA Bipod. This product is designed to provide stable shooting support for your firearm. To ensure safe and effective use, please read and follow these safety instructions carefully.

General Safety Guidelines

- Always ensure that the bipod is securely attached to the firearm before use.
- Inspect the bipod for any signs of damage or wear before each use.
- Use the bipod only with compatible firearms that have a sling swivel stud.
- Keep the bipod out of reach of children and vulnerable individuals when not in use.
- Report any unsafe products or incidents to the relevant authorities.

Specific Safety Precautions for Use

- Ensure the bipod is adjusted to the correct height for your shooting position.
- Do not exceed the weight limit of the bipod as specified by the manufacturer.
- Avoid placing excessive force on the bipod when in use, as this may cause instability.
- Always be aware of your surroundings and ensure a safe shooting environment.
- If using the pivot model, ensure that the pivot mechanism is functioning correctly before use.

Instructions for Installation and Usage

Installation

1. Locate the sling swivel stud on your firearm.
2. Align the bipod attachment with the sling swivel stud.
3. Securely attach the bipod to the firearm by tightening the locking mechanism.
4. Confirm that the bipod is firmly attached and does not wobble.

Usage

- Adjust the legs of the bipod to the desired height by using the notched indexing feature.
- Ensure that the bipod is stable on the ground before placing your firearm on it.
- If using the pivot model, engage the pivot feature to allow for lateral movement.
- Always check that the bipod is stable and secure before taking any shots.

Disposal Instructions

- Dispose of the bipod in accordance with local regulations.
- If the bipod is damaged beyond repair, consider recycling materials where possible.
- Do not dispose of the bipod in regular household waste.

Contact Information for Further Support

For any inquiries regarding product safety or support, please refer to the manufacturer's contact information found in the product packaging or on the official website.

By following these safety instructions, you can ensure a safe and enjoyable experience with your Caldwell XLA Bipod. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk