

# **XLA 6-9" Bipod - Fixed Model, Black - XLA 13 1/2 - 27" Bipod - Pivot Model, Camo**

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

The Caldwell® XLA Bipod® provides a stable shooting support that conveniently attaches to almost any firearm with a sling swivel stud. The legs are notched for easy indexing to a specific height. The bipods are available in 4 heights, black or camo and in both standard and pivoting models.

NO IMAGE  
AVAILABLE

## **Attributes**

- Name: [XLA 13 1/2 - 27" Bipod - Pivot Model, Camo](#)
- Manufacturer: [Caldwell](#)
- Product no.: EU1001896
- Mfr. No.: 445088
- Colour: Black
- Style: Bipod
- Delivery weight: 0.64kg
- Shipping height: 146mm
- Shipping width: 61mm
- Shipping length: 437mm
- UPC: 661120450887

# Table of Contents

- Startpage
- Caldwell XLA Bipod Safety Instructions
- About Us

# Caldwell XLA Bipod Safety Instructions

## Introduction

Thank you for choosing the Caldwell XLA Bipod. This product is designed to provide stable shooting support for your firearm. To ensure safe and effective use, please read this safety instruction guide carefully. It is essential to follow all guidelines to maximize safety and performance.

## General Safety Guidelines

- Always treat every firearm as if it is loaded.
- Ensure that the bipod is securely attached to the firearm before use.
- Inspect the bipod for any signs of damage or wear before each use.
- Use the bipod only with compatible firearms that have a sling swivel stud.
- Keep the bipod out of reach of children and unauthorized users.
- Do not exceed the weight limit of the bipod; refer to the product specifications for details.
- Be aware of your surroundings and ensure a clear shooting area.
- Use appropriate eye and ear protection while shooting.

## Specific Safety Precautions for Use

- **Stability:** Ensure the bipod legs are fully extended and locked in place before shooting.
- **Height Adjustment:** Adjust the bipod legs to the desired height by using the notches provided. Ensure they are securely locked after adjustment.
- **Surface:** Use the bipod on stable and level surfaces to prevent tipping or sliding.
- **Weather Conditions:** Avoid using the bipod in extreme weather conditions that may affect stability and performance.
- **Maintenance:** Regularly clean and maintain the bipod to ensure optimal performance and longevity.

## Instructions for Installation and Usage

### Installation

#### 1. Attach the Bipod:

- Locate the sling swivel stud on your firearm.
- Align the bipod attachment with the sling swivel stud.
- Firmly attach the bipod by securing the locking mechanism.

#### 2. Adjust the Legs:

- Press the release button on each leg to allow for extension.
- Pull the legs down to the desired height.
- Release the button to lock the legs in place.

### Usage

#### 1. Positioning:

- Place the bipod on a stable surface.
- Ensure the firearm is securely positioned in the bipod cradle.

#### 2. Shooting:

- Confirm your shooting position and target.
- Maintain a firm grip on the firearm and ensure proper stance.
- Fire only when you are sure of your target and what is beyond it.

## **Disposal Instructions**

- Dispose of the bipod in accordance with local regulations.
- Do not dispose of the bipod in household waste.
- Check with local waste management authorities for proper disposal methods.

## **Contact Information for Further Support**

For any safety inquiries or concerns regarding the Caldwell XLA Bipod, please consult the product packaging for the appropriate contact information. Ensure you have the model number and purchase details ready for assistance.

Thank you for your attention to these safety instructions. Your safety is our priority. Enjoy your shooting experience with the Caldwell XLA Bipod!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)