

AR Safety Black

[Rifle Parts](#) > [Triggers Parts](#) > [Triggers](#)

Material Details

1. Tumbler: 440C Stainless Steel & DLC Coated - Diamond-like Carbon Coating. This finish has unique properties of natural diamond - low friction, high hardness, and high corrosion resistance.
2. Levers: 17-4 Stainless Steel. The Black version is coated with PVD - Physical Vapour Deposition. It is a hard and durable coating that is applied to external stainless components to give them a clean black color.
3. Detent: 440C Stainless Steel.
4. Detent Ball Tip: Silicon Nitride - ultra low friction and extremely durable to provide smooth surface that will never wear.

NO IMAGE
AVAILABLE

Description

The AR Safety was developed to maximize the performance with TriggerTechs AR triggers and loaded with features. The patented design allows the safety to be installed and removed without removing the grip (after initial install). This is made possible by the tumbler and ball tipped detent pin. This feature saves time when changing triggers, cleaning or performing maintenance on your firearm. The detent has a silicon nitride ball tip which offers extremely low friction and durability, which gives an unmatched smooth feel when changing from safe to fire. The same material used on the bottom of space shuttles! The safety is ambidextrous with interchangeable short and long levers. A cap is provided to install on one side if the user wishes to only have a lever on one side. It can easily be setup as a 45 ° or 90 ° degree throw. The tumbler is made of 440C stainless steel and DLC coated for ultra performance and durability. The levers are constructed from 17-4 stainless steel and the black version is coated with PVD. This product is a must have for any competitive shooter looking to up their game!

Attributes

- Name: [TRIGGERTECH AR Safety Black](#)
- Manufacturer: [TRIGGERTECH](#)
- Product no.: EU2010008
- Mfr. No.: ARS-SNB-49-YCM
- Style: Ambidextrous
- Weapon type: AR-15
- Delivery weight: 0.13kg
- Shipping height: 38mm
- Shipping width: 102mm
- Shipping length: 178mm
- UPC: 885768001250

Table of Contents

- Startpage
- TRIGGERTECH AR Safety Trigger Safety Instruction Guide
- About Us

TRIGGERTECH AR Safety Trigger Safety Instruction Guide

Introduction

Thank you for choosing the TRIGGERTECH AR Safety Trigger. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your product. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the AR Safety Trigger is installed correctly according to the provided instructions.
- Always handle firearms safely and responsibly.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the trigger and safety mechanism for wear and tear.
- Do not modify the product in any way that may affect its performance or safety.
- Report any unsafe products or accidents to the relevant authorities.
- Stay informed about recall updates through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always ensure the firearm is unloaded before installing or adjusting the safety trigger.
- Use caution when changing from safe to fire to avoid accidental discharge.
- Ensure that the safety lever is fully engaged in the "safe" position when not in use.
- If you experience any resistance or unusual movement during operation, stop use immediately and inspect the product.
- The product is designed for adult users; keep it away from children.

Instructions for Installation and Usage

Installation

1. Initial Setup:

- Ensure you have the appropriate tools for installation.
- Read through the installation manual provided with the product.

2. Removing the Grip:

- Follow the manufacturer's instructions to remove the grip from your firearm.
- Ensure the firearm is unloaded before proceeding.

3. Installing the Safety Trigger:

- Insert the tumbler into the designated slot.
- Align the balltipped detent pin with the tumbler.
- Secure the safety trigger in place, ensuring it is properly seated.

4. Reinstalling the Grip:

- Carefully reattach the grip to the firearm.
- Ensure all screws and components are tightened according to the manufacturer's specifications.

Usage

- To engage the safety, push the lever to the "safe" position.
- To disengage the safety, push the lever to the "fire" position.
- The safety can be set for a 45° or 90° degree throw based on user preference.
- If you wish to use only one lever, install the provided cap on the unused side.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Contact local waste management authorities for proper disposal methods.

Contact Information for Further Support

For additional support or inquiries regarding the TRIGGERTECH AR Safety Trigger, please refer to the manufacturer's website or contact their customer service directly.

By following these guidelines and instructions, you can ensure the safe operation and longevity of your TRIGGERTECH AR Safety Trigger. Thank you for prioritizing safety and responsible firearm handling.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk